



Part Number:	<b>TE044003-4</b>	
DRAWN	CJ	7/20/2019
CHECKED	C.H.	7/22/2019
Description:	<b>Electro-Mechanical Transducer</b>	
APPROVED	C.E.	7/22/2019
<small>This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at <a href="http://www.dbunlimitedco.com">www.dbunlimitedco.com</a></small>		


Top View




Side View



Bottom View



Land Pattern



Items	Specifications	Conditions
Min. Sound Pressure Level	70	dB (@ 10cm)
Resonant Frequency	4,000	Hz
Rated Voltage	3	V
Voltage Range	2 ~ 4	V
Coil Resistance	17	Ω
Max. Rated Current	90	mA
Storage Temperature	-40 ~ +85	°C
Operating Temperature	-40 ~ +85	°C
Connection Method	Surface Mount Pads	
Mount Type	Surface Mount	
Housing Material	LCP	
Weight	0.1	g

**CONFIDENTIAL - DO NOT DISSEMINATE**

REVISION HISTORY

REV	DESCRIPTION	DATE	APPROVED
	Released from Engineering	7/22/2019	C.E.

NOTES

- 1) All dimensions are in mm unless otherwise noted
- 2) All tolerances are ± 0.5 mm unless otherwise noted
- 3) All parts meet RoHS
- 4) Subject to change or redrawn without notice