



Recommended PCB Layout  
(Bottom View)

**Materials and Finish**

Housing: PBT Thermoplastic  
15% Glass Filled, Black Color  
UL 94V-0 Rated

Terminals:  
Pin #1: Brass, Nickel Plated  
Pin #5 & Pin #2:  
Phosphor Bronze, Matte Tin Plated  
Pin #3 & Pin #4:  
Brass, Matte Tin Plated  
Slide Switch Terminals:  
Brass, Silver Plated

Bushing: Brass, Nickel Plated

**Electrical Characteristics**

Rated Voltage: DC 24 V

Rated Current: 3.0 A

Contact Resistance:  
Before Test: 50mohms Max.  
After Durability Test: 100 mohms Max.

Insulation Resistance:  
More Than 100 Megohms  
At 500V DC

Dielectric Strength:  
500V AC RMS for 1 Minute

Operating Temp: -25°C to +85°C

**Mechanical Characteristics**

Insertion Force: 0.3kg - 3.0kg

Extraction Force: 0.3kg - 3.0kg

Durability: 5000 Mating Cycles Min.

Tolerances
X.X ± 0.3
X.XX ± 0.15
Unless Stated
Otherwise

**RoHS COMPLIANT**

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	02/08/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	02/08/06
B1	07/24/09	ECO #09-046	S. Vien	H. MA		
B2	07/14/11	ECO #11-033	S. Vien	P. DalCanto		
B3	06/04/13	ECO #13-028	W. Cook	P. DalCanto		
B4	04/12/18	ECO #18-017	J. Elbanna	C. Kelleher		
B5	04/19/19	ECO #19-035	C. Kelleher	D. Shehan		

**STX-3100-11C**

Ø3.5mm Stereo Jack, Male, RoHS Compliant

With Double Throw, Double Pole Switch

