


**SACC-FS-4QO-0,34-M SCO**

Order No.: 1521588

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1521588>Sensor/actuator connector, socket, straight, 4-pos., M12 SPEEDCON,  
A-coded, QUICKON-ONE, metal knurl, cable diameter max. 6 mm

Commercial data	
GTIN (EAN)	 4 017918 953058
sales group	D121
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 48 (PC-2009)

## Product notes

WEEE/RoHS-compliant since:  
11/13/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Rated current at 40°C	4 A
Rated voltage	125 V
Number of positions	4
Volume resistance	≤ 5 mΩ


Insulation resistance	≥ 100 MΩ
Ambient temperature (operation)	-25 °C ... 80 °C (Male connector / female connector)

**General characteristics**

Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65/67
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA 66
Material of grip body	PA 66
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Type of connection	QUICKON fast connection
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	0.34 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	22
Wire diameter including insulation	0.7 mm ... 1.6 mm
Frequency of connections between conductors of the same cross section	10
External cable diameter	3.5 mm ... 6 mm
Wire insulation material	PVC/PE/PP
Tightening torque, union nut	0.8 Nm
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	Class 2-6
Status display	No


## Diagrams/Drawings

### Dimensioned drawing



M12 x 1 female connector, straight

### Schematic diagram



Pin assignment M12 socket, 4-pos., A-coded, view female side

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;