



Astro compact scales offer a full set of features for easy weighing in classrooms, industrial applications and portion control. With capacities ranging from 2000g to 8000g, the Astro is ideal for measuring food servings or quantities of ingredients for recipes or science experiments. Solid, one-piece construction and stainless steel housing are easy to clean, while the durable grade 304 stainless steel pan accommodates ingredients or a weighing container. Astro is simple to operate, with only two buttons that provide ready access to the weighing units and allow the unit to be tared quickly. Results are shown in green on the Astro's large LCD. If too much weight is placed on the scale, the green figures change to red, alerting the user.

A sleek portioning scale,
easy to clean between weighing tasks



Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Colored LCD displays green when weighing and red at overload
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows swift cleaning
- Overload protection helps prevent damage to internal components
- Rugged stainless steel construction for ultimate durability
- Auto power-off to save energy
- External calibration allows for verification and adjustment with weights
- Operates with AC adapter (included) or batteries (not included)
- Low-battery indicator alerts users when batteries need replacement

Applications

- Weighing

About ADAM:

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

AstroTM Compact Portioning Scale



| Model | ASC 2001 | ASC 4000 | ASC 8000 |
|--------------------------|--|----------|----------|
| Capacity | 2000g | 4000g | 8000g |
| Readability | 0.1g | 0.5g | 1g |
| Pan Size | 6.3"x7.1" / 160x180mm | | |
| Weighing Units | g, lb, oz | | |
| Stabilization Time (sec) | 2 | | |
| Calibration | External calibration | | |
| Display | LCD with 0.7" / 18mm-high digits | | |
| Power Supply | 6VDC 500mA adapter / 2 x AAA batteries | | |
| Operating Temperature | 0° to 40°C / 32° to 104°F | | |
| Housing | Stainless steel | | |
| Overall Dim. | 8.3"x6.6"x2.6" / 212x167x66mm (wxdxh) | | |
| Net Weight | 1.9lb / 0.85kg | | |

Supplied by

www.adamequipment.com

Adam Equipment follows a policy of continuous improvement and reserves the right to change specification and pricing without notice. Adam Equipment's standard terms and conditions of sale apply. Errors and omissions excepted.

©2016 Adam Equipment. NA-6062