

W-GYK, Thread-Mountable Pt Temperature Sensor according to DIN EN 60751

Temperature range -40 °C to +250 °C

- Simple mounting via integrated G1/8 thread
- High thermal conductivity brass housing provides good thermal transfer
- Rugged PTFE-insulated connection wires

The thread-mountable sensor is easily mounted with a mating threaded hole, resulting in a secure installation with effective thermal contact. Possible applications include temperature measurement in mechanical systems, HVAC, and electronics. The housing material is resistant to oils, fats, organic and inorganic bases and alkalis (medium concentration) and protects the sensor from mechanical damage.

Nominal Resistance R ₀ [Ω]	Tolerance Class	Order Number
Pt100	F 0.3 / Class B	30010007
Pt1000	F 0.3 / Class B	30010000

Temperature and Tolerance Range

Tolerance Class F 0.3 / B -40 °C to +250 °C

Temperature Coefficient

TCR = 3850 ppm/K

Connection Wire

PTFE insulated Ni wire
2x∅ 0.4 mm (=26 AWG), 180 mm long

Internal Conductor Resistance

0.27 Ω ± 25 %

Housing

Hex screw with G 1/8 thread, brass 2.0401 (MS58)
Width across hex flats : 13 mm

Applications

Temperature sensing in

- Heat sinks
- Motor casings
- Bearing casings
- Mechanical equipment



Image for illustration purposes only

W-GYK, Thread-Mountable Pt Temperature Sensor according to DIN EN 60751

Temperature range -40 °C to +250 °C

Features

- Easy surface mounting via integrated G 1/8 thread
- Brass housing provides good thermal transfer
- Rugged PTFE insulated connection wires
- Available in Pt100 and Pt1000 resistance values
- +250 °C maximum operating temperature

Options

- Wire length
- Resistance Value
- Connectors

Resistance vs Temperature Table

Reference table @ www.herae.us/technical-information




Image for illustration purposes only



The information provided in this data sheet describes certain technical characteristics of the product, but shall not be qualified or construed as quality guarantees whatsoever. Furthermore, the information provided in this data sheet does not constitute a warranty, implied or express, whatsoever, including but not limited to warranties of merchantability, fitness for a particular purpose, or use. The information provided in this data sheet regarding measurement values (including, but not limited to, response time, long-term stability, vibration and shock resistance, insulation resistance and self-heating) are average values that have been obtained under laboratory conditions in tests of large numbers of the product. Product results or measurements achieved by customer or any other person in any production, test, or other environment may vary depending on the specific conditions of use.

The customer is solely responsible to determine whether the product is suited for customer's intended use; in this respect Heraeus cannot assume any liability. The sale of any products of Heraeus is exclusively subject to the Terms and Conditions of Sale of Heraeus in their current version at the time of purchase, which is available under www.heraeus.com/gtc or may be furnished upon request. This data sheet is subject to changes without prior notice.

Heraeus Nexensos USA, a division of Heraeus Epurio LLC, 770 Township Line Road, Suite 300, Yardley, Pennsylvania, USA 19067