



Product: <u>6328UL</u> ☑

Fire Alarm, #18-10c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 10-18 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Product Ov			Size		ation Oissuite Asselie	Analysis in February Matthewstrum	
Suitable Applications: Fire				re Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification			
Constructi	on Details						
Conductor							
Element	No. of Elements	s Size	Stranding	Material			
Conductor(s)	10	18 AWG	6 Solid	BC - Bare Copper			
nsulation							
Element	Material	١	lom. Thickne	ss Nom. Insulation	on Diameter	Color Code	
Conductor(s)	PVC - Polyvinyl Chloride	C).01 in (0.25 m	m) 0.0605 in mm	Black,	Red, Brown, Blue, Orange, Yellow, Purple, Green, Red/Black, Red/Whit	
Outer Shield							
Material							
No Shield							
Outer Jacket							
Mater		n. Thickne					
	yl Chloride 0.015		nm) 0.272 in	Yes			
Overall Cable	Diameter (Nomin	al):	0.272	2 in			
Electrical (Characteristi	cs					
Electricals							
Nom. Conduc		Capacitan (ft (95 pF/m	ice Cond-to-C		k. Current		
0.4 0111/1000	ла 29 рг/	it (95 pr/ii	1)	3.5 Amps per	Conductor at 25°C		
/oltage							
UL Voltage R	ating						
300 V							
Mechanica	I Characteris	stics					
		51103					
Femperature							
UL Temperat	ure Operating						

75°C 0°C To +75°C

Bend Radius

 Stationary Min.
 Installation Min.

 2.176 in (55.27 mm)
 2.176 in

Max. Pull Tension:	196 lbs (88.9 kg)		
Bulk Cable Weight:	73.5 lbs/1000ft		

Standards and Compliance

Environmental Suitability:	Indoor			
Flammability / Reaction to Fire:	NFPA 262 (UL 910)			
NEC / UL Compliance:	Article 760, FPLP			
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			
Other Standard Compliance(s):	California State Fire Marshall			
Non-Plenum Number:	5328UL			

History

Update and Revision:

Revision Number: 0.306 Revision Date: 05-05-2023

Part Numbers

Variants

ltem #	Color	UPC	Footnote	
6328UL 0021000	Red	612825176039	С	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.