


Cable Ties/High Temperature Ties

HellermannTyton's high temperature cable ties provide excellent resistance in operating temperatures up to 275°F (135°C), while still maintaining tensile strength properties.



| Material Data | |
|-----------------------|---|
| Material | Polyamide 4.6 (PA46) |
| Operating Temperature | -40 °F to +275 °F (-40 °C to +135 °C) continuous |
| Flammability | UL94 V2 |



| Product Selection | | Type | Min. Tensile Strength | Length (L) | Max Ø Bundle | Width (W) | Color | Pkg. Qty. |
|-------------------|--------------------|-------------|-----------------------|-------------|--------------|------------|-------|-----------|
| Article No. | Part No. | | lbs. (N) | in. (mm) | in. (mm) | in. (mm) | | |
| 116-01811 | T18R1STNLM5 | T18R1STNLM5 | 18 lbs. (80) | 4" (100) | .87" (22) | .10" (2.5) | Brown | 100 |
| 116-03011 | T30R1STNLM4 | T30R1STNLM4 | 30 lbs. (135) | 5.9" (150) | 1.38" (35) | .14" (3.5) | Brown | 100 |
| 116-05011 | T50R1STNLM5 | T50R1STNLM5 | 50 lbs. (225) | 7.9" (200) | 1.97" (50) | .18" (4.6) | Brown | 100 |
| 111-05443 | T50L1STNLM4 | T50L1STNLM4 | 50 lbs. (225) | 15.3" (390) | 4.33" (110) | .18" (4.6) | Brown | 100 |