

## Specification Sheet

Part Number: 151-00018



Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.

Extended fir tree allows for a wide range of panel thicknesses.

Fir tree design provides low insertion forces and high extraction forces.

Convoluted Tubing Clip, 0.4" Max Bundle Diameter, Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

Article Number 151-00018

Type CTC10FT6LG

Color Black (BK)

Quantity Per bag

Product Description Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.

Short Description Convoluted Tubing Clip, 0.4" Max Bundle Diameter, Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

Global Part Name CTC10FT6LG-PA66HIRHS-BK

|   |              |
|---|--------------|
| Fixation Method                         | Fir Tree     |
| Variant                                 | Clips        |
| Width W (Imperial)                      | 0.31         |
| Width W (Metric)                        | 8.0          |
| Height H (Imperial)                     | 0.85         |
| Height H (Metric)                       | 21.4         |
| Nominal Diameter (Imperial)             | 0.38         |
| Nominal Diameter (Metric)               | 10.0         |
| Panel Thickness Min (Imperial)          | 0.03         |
| Panel Thickness Max (Imperial)          | 0.24         |
| Panel Thickness Min (Metric)            | 0.75         |
| Panel Thickness Max (Metric)            | 6.0          |
| Mounting Hole Diameter D (Imperial)     | 0.26 - 0.28  |
| Mounting Hole Diameter D (Metric)       | 6.5 - 7.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.283        |
| Mounting Hole Diameter D Max (Imperial) | 0.275        |

|                                       |  |
|---------------------------------------|--|
| Mounting Hole Diameter D Max (Metric) | 7.0  |
| Disc Diameter (Metric)                | 16.0   |
| Disc Diameter (Imperial)              | 0.63   |
| Material                              | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut                     | PA66HIRHS  |
| Flammability                          | UL 94 HB   |
| UV Resistant (Yes/No)                 | No   |
| Operating Temperature                 | -40°F to +221°F (-40°C to +105°C)                                |
| Reach Compliant (Article 33)          | Yes  |
| ROHS Compliant                        | Yes  |
| Package Quantity (Imperial)           | 500  |
| Package Quantity (Metric)             | 500  |
| Customs Number                        | 3926909988   |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)