VIEW ON MATING SIDE

	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
c		C		C		C		C		C		C		C		C		C		C		C		C		C		C		C		C
b																																
a	A		A		A		A		A		A		A		A		A		A		A		A		A		A		A		A	

A = 16 STANDARD CONTACTS L = 3
C = 16 STANDARD CONTACTS L = 3

S = 32 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G3/0 = CONTACT AREA LEVEL 3 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

C	G3/0	c1+3+5+7 31
A	G3/0	a2+4+6+8 ...32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. 1 2004-XXXX
DRWN N.S. 09/09/03
CHKG G.L. 09/09/03
APPR G.L. 09/09/03
DESCRIPTION
C
REV

QUALITY SYMBOLS
MAJOR
CRITICAL

GENERAL TOLERANCES: (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±0.	±.
3 PLACES	±0.	±.
2 PLACES	±0.	±.
1 PLACE	±0.	±.
ANGULAR: ±		°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

SCALE
DESIGN UNITS ☒mm ☐INCH
THIRD ANGLE PROJECTION
DIMENSIONS: ☐ mm/INCH ☐ INCH/mm ☒ mm ONLY
SHT REV
REVISE ON CAD ONLY

DRAWN BY & DATE N.S. 15/04/02
CHECKED BY & DATE G.L. 15/04/02
APPROVED BY & DATE G.L. 15/04/02

TITLE: 96 POS MALE CONNECTOR
ACCORDING DIN 41612 STYLE C
CONTACTS ARRANGEMENT

MOLEX INCORPORATED

CAD FILENAME $D-85003-9023.S01
MATERIAL NO. 85003-9023
DRAWING NO. SD-85003-9023
SHEET NO. 1 OF 1
SIZE D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.