

AMP | AMPSEAL 16

TE Internal #: 2040594-6

Housing for Male Terminals, Wire-to-Wire, 12 Position, .177 in [4.5

mm] Centerline, Sealable, Black, -40 – 257 °F [-40 – 125 °C],

AMPSEAL 16
View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > AMPSEAL 16 Housings











Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.5 mm [.059 in]

Connector System: Wire-to-Wire

Number of Positions: 12

Centerline (Pitch): 4.5 mm [.177 in]

All AMPSEAL 16 Housings (226)

Features

Product Type Features

Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	12
Number of Rows	2
Body Features	
Primary Product Color	Black



Contact Size	Size 16
Contact Type	Pin
Mating Pin Diameter	1.5 mm[.059 in]
Mechanical Attachment	
Terminal Position Assurance	No
Mating Alignment Type	Polarizing Tab
Mating Alignment	With
Housing Features	
Centerline (Pitch)	4.5 mm[.177 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 81 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][173 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Industry Standards	
Degree of Protection	IP67
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	160
Packaging Method	Box
Other	
Connector Position Assurance Capable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per



homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-AM7801-CH8172

AMPSEAL 16 Housings



TE Part # CAT-AM7801-B128

AMPSEAL 16 Connectors Backshell



TE Part # CAT-AM7801-T273 Contacts: Size 16, 13A





Also in the Series | AMPSEAL 16



Automotive Connector Caps & Covers (85)



Automotive Connector Locks & Position Assurance(2)



Automotive Housings(244)



Automotive Terminals(33)










Data Connectivity Headers(2)



Data Connectivity Housings(3)



Other Automotive Connector Accessories(11)

Customers Also Bought



TE Part #1717934-2

AMPSEAL 16 Housings



TE Part #1717138-4
TH/.025 CONNECTOR SYSTEM,
HOUSING



TE Part #2292865-2 AS16 BACKSHELL, 12P CAP, NC20, MC



TE Part #HDP26-24-16PE-L017 PLG, 16P, BLK, E, RNG, 12, P



Documents

Product Drawings

SEAL CAP HSG 12P, AMPSEAL16 SE

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_2040594-6_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2040594-6_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2040594-6_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Male Terminals, Wire-to-Wire, 12 Position, .177 in [4.5 mm] Centerline, Sealable, Black, -40 – 257 °F [-40 – 125 °C], AMPSEAL 16



Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

Product Specifications

AMPSEAL SEAL CAP

Japanese

Product Specification

Japanese