



Recommended Cable Stripping Dim's

Crimped Ferrule
Hex. Crimp Size .213 (5.4)
Contact Pin to Solder

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min, Thick
 3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
 4. Teflon
 5. Passivated

RoHS Compliant

10	Ferrule	Copper	Note 2	1	
9	Nut		Note 1	Note 2	1
8	Barrel		Note 1	Note 2	1
7	Contact Pin		Note 1	Note 3	1
6	Retainer Ring	SUS 304	Note 5		1
5	Gasket	Silicone	Red		1
4	Contact Body		Note 1	Note 2	1
3	Insulator		Note 4	Natural	1
2	Body		Note 1	Note 2	1
1	Shell		Note 1	Note 2	1

Dimensions are in Inches			
Unless Otherwise Specified Tolerances			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	
No.	Description	Material	Finish
			Q'ty
			Drawing No.
			Scale
			Issue
			A

Part No.		<h1>NTE Electronics</h1>
Approved	Date	
Checked	Date	
Drawn	Date	
Title		N R/A Crimp Plug (For RG-58, 58A, 58C, 141, LMR195)
Drawing No.		06-N007
File No.		