

940 Receptacle

speedtec - ready

Earth-to-Housing Connection according to VDE 0627 flange mount /Flange 40x40 Anti-vibration o-ring

Technical Data

number of pins

-20 °C to 130 °C temperature range protection type

when connected IP 66/67

Electrical Data power signal rated current rated voltage max. 75 A* 630V (AC/DC) max. 30 A* 250 V (AC/DC) rated insulation voltage (L-L) 6000 V 4000 V

500 mating cycles

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree over voltage category TTT max. height for operation 2000 m

Material

zinc diecast / nickel plated

insulation insert PA, UL 94/V0

seals

Contacts (not part of product contents)

Tools (not part of product contents)

C EG A 257 NN 00 00 0056 000 C E A 257 N 00 00 0056 000



Contact Arrangement mating view



© 2018 TE Connectivity


TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.


While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are publied to chance without in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH

Be Conhectivity Industrial Gmbh Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel.: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mail: intercontec@te.com Web: www.intercontec.biz







Main Dimensions Receptacle

*for max, wire cross-section pay attention to the cross-section of used contacts