


FILE

REVISIONS

LTR	DESCRIPTION	DATE	APPROVED



PROPRIETARY INFORMATION
NOT TO BE RELEASED
WITHOUT WRITTEN PERMISSION
FROM AN AUTHORIZED
REPRESENTATIVE OF
APPLIED ENGINEERING PRODUCTS.

NOTES:

MATERIAL:

- CONTACTS = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.
- INSULATORS = TEFLON, VIRGIN WHITE PER ASTM D1710, GRADE 1, TYPE I, CLASS A.
- ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

FINISHES:

- CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C OVER STRESS FREE SULFAMATE NICKEL PER QQ-N-290.
- ALL OTHER METAL PARTS = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C OVER .00010 TO .00020 COPPER STRIKE PER MIL-C-14550.

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN INCHES
TOLERANCES ON

FRAC. 1/64 DECIMAL ANGLES ± 2°

MATERIAL:

SEE NOTES

DRAWN D.N. DATE 4-18-97

CHECKED DATE 4/12/97

APPROVED DATE 4-18-97

FINISH:
SEE NOTES

APPLIED ENGINEERING PRODUCTS

104 John W. Murphy Drive, P.O. Box 510
New Haven, CT 06513

SSMB PRINTED CIRCUIT BOARD
RIGHT ANGLE JACK RECEPTACLE
WITH TIN DIPPED LEGS AND CENTER PIN

SIZE
A

CODE IDENT NO.
19505

7210-1511-012

SCALE NTS

SHEET 1 OF 1