



Spring Loaded Contacts  
With PRECI-DIP Integrated CLIP



NOTES:

MECHANICAL REQUIREMENTS:

Durability: 20'000 cycles at Hnom  
Theoretical stroke: S= 1.4 mm [.055"]  
Spring forces (F):  
Finit= 0.50 N at Hinit= 11.05 mm [.435"]  
F1= 0.57 N at H1= 10.85 mm [.427"]  
Fnom= 0.75±0.15 N at Hnom= 10.15 mm [.400"]  
F2= 1.07 N at H2= 9.45 mm [.372"]  
Recommended working range: between H1 and H2  
Forces are measured in mean value of compression / decompression  
\* Theoretical values of spring design

ELECTRICAL REQUIREMENTS:

Contact resistance:  
R= 30 mOhms max in static mode at Hnom  
Current per individual contact in free air at ambient temperature:  
ICont= 5 A at Hnom with temperature raise max 30°C

ENVIRONMENTAL REQUIREMENTS:

Operating temperature: -25 °C / +125 °C  
Storage temperature: -40 °C / +125 °C  
Relative humidity: 5% / 95%

MATERIALS / PLATINGS:

Contact interfaces plated with 0.5 µm [20µ"] gold over Nickel  
Spring: Stainless steel  
Clip : Beryllium Copper

SOLDERING :

Recommended PCB pad size : 2.0 mm [.078"]  
Solderability J-STD-002A, Test A 245°C, 5s, solder alloy SnAg3.8Cu0.7  
Resistance to soldering heat J-STD-020C, 260°C, 20S

INSULATOR :

If assembling pin into moulding :  
Recommended hole size : Ø1.58[.062"]

High Reliability  
Spring Loaded Contact



Remplace:

Remplacé par:

25:1

Dessiné

15.12.2022

C.Bidault

Contrôlé

N° dessin

Révision

0907-9-CLIP