

## Panel mounting frame set - CUC-V04-F-BU/BU-RJ45 - 1407412

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel mounting frame set, Degree of protection: IP65/67, Number of positions: 8, Material: Plastic



### Key Commercial Data

Packing unit	1 STK
Custom tariff number	85366990
Country of origin	Romania

### Technical data

#### Mechanical characteristics

Standards/specifications	IEC 61076-3-106
Number of positions	8
Connection profile	RJ45
Locking type	Push Pull
Insertion/withdrawal cycles	≥ 750
Color	black

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65

#### Material data

Flammability rating according to UL 94	V0
Housing material	Plastic

#### Electrical characteristics

# Panel mounting frame set - CUC-V04-F-BU/BU-RJ45 - 1407412

## Technical data

### Electrical characteristics


Number of positions	8
---------------------	---

### Standards and Regulations

Standards/regulations	IEC 61076-3-106
Flammability rating according to UL 94	V0

## Drawings

Dimensional drawing



Panel mounting frame dimensional drawing

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261207
eCl@ss 7.0	27440210
eCl@ss 8.0	27440210
eCl@ss 9.0	27440210

### ETIM

ETIM 3.0	EC002310
ETIM 4.0	EC002310
ETIM 5.0	EC002310

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501

## Panel mounting frame set - CUC-V04-F-BU/BU-RJ45 - 1407412

### Classifications

#### UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

---

#### Approval details

EAC B.01742
-------------

### Accessories

#### Accessories

#### Data plug

RJ45 connector - CUC-V04-RJ45-POBK-8 - 1407413



RJ45 connector, IP65/IP67, with push/pull interlocking (version 4), plastic housing, for 10 Gbps, for 24 ... 28 AWG stranded conductors