


Insulation Thickness 0.76mm
Overall Diameter 3.6±0.10mm

Copper Conductor
41/0.26±0.004mm
Resistance 8.88
(20° (Max). ohms/km)

Jacket Thickness 0.76mm
Overall Diameter 9.3±0.15mm



Black
White
(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip		
Color	Component	Qty	Strip	ROJ	Color		Strip	ROJ	Color
40P Black 90±5° A	LT-202(15A 125V) (NEMA5-15P)	1	7±1	23±3	Black	SJT 14AWGX3C 105°C BLACK Length: 1000±50 mm	$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Black
Nickel-Plated	Plug Terminal	1	7±1	23±3	White		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	White
Nickel-Plated	UL Blades	2	7±1	26±3	Green		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Green
White	(202 Inner Body)	1							

NOTE :

1. PLUG : LT-202 AMERICAN TYPE
2. CONNECTOR : NA
3. CORD : SJT 14AWGX3C 105°C BLACK 1M
4. APPROVALS : UL C-UL
5. Supplier for flexible cord : RHYTHM
6. Hi-Pot Test:2000v/1min<1mA>

Marking:

RHYTHM: (UL) E88231 SJT 3X14AWG(2.08mm²)
105°C 300V VW-1 CSA LL54496 SJT
3X14AWG(2.08mm²)105°C 300V VW-1
RHYTHM R

Modification History

NO.	DESCRIPTION	DATE

DRAWER	Eric	DATE	20/10/17	P/N	800-1401-2-SJT0-BL-00100-1
APPROVE		REV.	0	Dr.No.	1091054
		TOL.			±5mm
		ALL DIMENSIONS IN mm			
		比例			

CnC Tech
Industrial Cable and Connector Technology