



Fork Board Lock Type

Directive 2002/95/EC
RoHS
Compliant

used for:

- Notes:
- Material And Finish
 - Shell: Steel, Nickel Plated
 - Bracket: Brass strip-H nickel plated
 - Screw: Brass nickel plated
 - Insulator-NYLDN 6T, UL-94V0, color black
 - PC 99: Colorful insulator
 - Pantone #661C: High Density 15 pos, Female
 - Contact: Phosphor bronze
 - Mating area: Gold plated
 - Sold Tails: Tin Plated

- Specifications
- Rated current: 5A max.
 - Rated Voltage: 300 VDC
 - Withstanding Voltage: 500 VAC (RMS) for 1 minute
 - Insulation Resistance: 1000 MΩm min. at 500 VDC
 - Contact Resistance: 13 mΩm max.
 - Dielectric Strength: 1000 VAC (RMS) for 1 minute
 - Temperature: -55 °C~+105 °C
- Operational Note:
- ①. Partmarking area to be degreased prior to marking operation

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION

<p>DO NOT ALTER CAD DRAWING BY HAND</p>		<p>tolerance unless otherwise specified</p>		<p>scale: SEE NOTES</p>	
<p>CONEC CORPORATION Brampton, Ontario</p>		<p>name date</p>		<p>material: D-Sub SMT 15 Female Connector</p>	
<p>author date</p>		<p>drawn date</p>		<p>drawing no.: AutoCAD 2004</p>	
<p>rev. / description</p>		<p>appd. date</p>		<p>part no.: C0410DD03A</p>	
<p>origin date</p>		<p>norm date</p>		<p>sheet 1/1</p>	
<p>name</p>		<p>name</p>		<p>DIN A3</p>	
<p>name</p>		<p>name</p>		<p>AutoCAD 2004</p>	
<p>name</p>		<p>name</p>		<p>1/1</p>	
<p>name</p>		<p>name</p>		<p>1/1</p>	

