

6 INCHES LENGTH



Connector A
132245
SMA Jack Right Angle
Bulkhead - Rear Mount Brass Gold + Heatshrink

50 Ohm RG-174
Continuity/Hi-Pot

Connector B
142186
SMB Plug Straight
Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.

Connector A		Cable		Connector B	
Part #:	132245	Part #:	RG-174	Part #:	142186
Description:	SMA R/A BHD JK RG174 RG316 LMR100	Description:	RG-174 - PE 0.1	Description:	SMB PLUG RG174 RG188 RG316 500
	500	Dielectric:	PE	Type:	SMB
Type:	SMA	Shielding:	Braid	Gender:	Plug
Gender:	Jack	Diameter:	0.1	Body Type:	Straight
Body Type:	Right Angle	Impedance:	50 Ohm	Contact Type:	Solder
Contact Type:	Solder	Sheathing:	None	Polarity:	Standard
Polarity:	Standard	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Impedance:	50 Ohm	Length:	6 Inches	Mounting:	Cable
Mounting:	Bulkhead - Rear Mount			Body Material:	Brass
Body Material:	Brass			Body Finish:	Gold
Body Finish:	Gold			IP Rating:	None
IP Rating:	None			Contact Material:	Beryllium Copper
Contact Material:	Beryllium Copper			Contact Finish:	Gold
Contact Finish:	Gold			Max. Freq.:	4 GHz
Max. Freq.:	12.4 GHz			Booting:	SMB Plug Straight
Booting:	SMA Jack Right Angle			Clocking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-RA-JK/SMB-ST-PL G174 6I

Part No:
Q-2P03W0003006I

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES