



114030K21MXXXG

Cable type
14/4 AWG
black TPE

Finished Length
M005 = .5 Meters
M010 = 1 Meter

MECHANICAL
CONTACT : GOLD/NICKEL OVER COPPER ALLOY
INSERT : BLACK PVC
COUPLING NUT: ZINC DIE CAST, BLACK E-COAT
MOLDED BODY: BLACK PVC
CABLE: 14 AWG 4 CONDUCTORS BLACK TPE JACKET
CABLE MARKING: [MFG. UL FILE NO.] 14 AWG (2.08mm²)
UL TYPE TC-ER/MTW (UL) THHN/THWN
600V 90C DRY 75C WET OIL RES SUN
RES [MFG. CSA FILE NO.] CSA AWM
I/II A/B 105C W75 1000V -40C FT4

ELECTRICAL
VOLTAGE RATING: 600V AC/DC
AMPERAGE: 15A

ENVIRONMENTAL
PROTECTION: IP67

| | | | | | | | | | |
|---|--------------------|-----------------------------------|---------------------------------------|---|-------------------------|---|-----------|-------------------|------------------------|
| UPDATED DRAWING EC NO: IPG2016-1628 DRWN: GGUSTAFS 2016/06/02 CHKD: MZIELINS 2016/06/15 APPR: BWOODMAN 2015/11/09 | DESCRIPTION REV | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE INCH/MM | | SCALE NTS | DESIGN UNITS INCH | THIRD ANGLE PROJECTION |
| | | $\nabla=0$ $\sphericalangle=0$ | mm | INCH | DRAWN BY DATE | TITLE | | | |
| | | 4 PLACES | ±--- | ±--- | KCOX01 2015/10/19 | MINI CHANGE ASSEMBLY 4P MALE/FEMALE 14/4 AWG TPE BLACK | | | |
| | | 3 PLACES | ±--- | ±--- | CHECKED BY DATE | | | | |
| | | 2 PLACES | ±--- | ±--- | BARDEN 2015/10/19 | | | | |
| 1 PLACE | ±--- | ±--- | APPROVED BY DATE | MOLEX INCORPORATED | | | | | |
| ANGULAR ±---° | | | MATERIAL NO. | DOCUMENT NO. | SHEET NO. | | | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | | SEE MATRIX | SD-130062-023 | 1 OF 1 | | | | |
| | | | SIZE B | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | |