211398-3 ACTIVE

AMP | AMP CPC

TE Internal #: 211398-3

Circular Power Connectors, Housing, 600 VDC, Wire-to-Wire, 7 Position, Sealable, Wire & Cable, Receptacle, Reverse Gender,

Socket, AMP CPC

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors

Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 7

Sealable: Yes

Features

Product Type Features

Connector Seal & Plug Type	Peripheral
Connector Product Type	Housing
Connector System	Wire-to-Wire
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Circular Connector Shell Type	All Plastic

Configuration Features

Reverse Numbering	Without
Number of Positions	7
Number of Power Positions	0
Number of Signal Positions	7

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Reverse Gender	Yes
Contact Type	Socket
Contact Protection	With

Mechanical Attachment



Mating Alignment Type	Keyed
Mating Alignment	With
Panel Mount Feature Type	Flange with Mounting Holes
Mating Retention Type	Threaded Coupling
Thread Size	3/4 - 20 UNEF-2A
Polarization Code	A
Connector Mounting Type	Panel Mount
Mating Retention	With
Panel Mount Feature	With
Housing Features	
Body Orientation	Straight
	Black
Housing Color	
Housing Color Housing Material	Nylon
	Nylon 13
Housing Material	
Housing Material Circular Connector Shell Size	
Housing Material Circular Connector Shell Size Usage Conditions	13
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range	13 -55 – 105 °C[-67 – 221 °F]
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance	13 -55 – 105 °C[-67 – 221 °F]
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application	13 -55 – 105 °C[-67 – 221 °F] Immersion
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application	13 -55 – 105 °C[-67 – 221 °F] Immersion Power & Signal
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded	13 -55 – 105 °C[-67 – 221 °F] Immersion Power & Signal
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards	13 -55 – 105 °C[-67 – 221 °F] Immersion Power & Signal No
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards Agency/Standard	13 -55 – 105 °C[-67 – 221 °F] Immersion Power & Signal No VDE
Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards Agency/Standard UL Flammability Rating	13 -55 – 105 °C[-67 – 221 °F] Immersion Power & Signal No VDE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

TE Part # 211400-1 CPC PLUG ASSEMBLY SIZE 13-7

Also in the Series	AMP CPC		
Circular Connector Adapters(7)	Circular Connector Caps & Covers(16)	Circular Connector Hardware(3)	Circular Connector Keying Plugs(2)



Circular Power Connectors(459)	Connector Backshells(56)	Connector Seals & Cavity Plugs(36)	Connector Strain Relief(6)
Insertion & Extraction Tools(1)	Power Contacts(6)	Sealing Sleeves(2)	
Customers Also B	Sought		
TE Part #211400-1 CPC PLUG ASSEMBLY SIZE 13-7	TE Part #T4144015051-000 M12 R/A M PNL REAR A-CODE 5P PCBSTD	TE Part #208211-1 SCREW SHOULDER, SPEC	TE Part #6-1393254-8 W92-X112-10=M6/M7/M9/W6/W7
TE Part #5206052-3 SCREW,SPECIAL,ZN	TE Part #1-796375-2 CPC PSTD RCPT,13-9,R/A LF	TE Part #2-1618240-7 K43C334=RELAY, VACUUM, SPDT	TE Part #60618-6 CMNL PIN AUPHBZ L/P
TE Part #NB13524001 RNF-100-3/8-BK-SP			

Documents



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_211398-3_AF.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_211398-3_AF.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_211398-3_AF.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Agency Approvals

UL Report

English