

Cat.6 UTP Cross Booted Cables Series

Technical Data Sheet CableMAX Model No. **CM-10072XGYBSTK**

Length 3ft. 7ft. 10ft. 15ft.	Green w/ Grey Wire CM-100723GYBSTK CM-100725GYBSTK CM-100726GYBSTK CM-100727GYBSTK
---	---

Specifications

** Information listed represents all cables within this series*

Conductor	Material / Size	Bare Copper / 24AWG
Insulation	Material	HDPE
	Thickness	Nominal: 0.20 mm
	Diameter	Nominal: 1.00 mm
	Colors	Blue/White-Blue Orange/White-Orange Green/White-Green Brown/White-Brown
	Unaged Elongation	Min. 300%
	Unaged Tensile Strength	Min. 1.683 Kgf/mm ²
Jacket	Material	Flame Retardant PVC
	Thickness	Nominal: 0.65 mm
	Diameter	Nominal: 7.5 mm
	Color	Assorted Upon Request
	Unaged Elongation	Min. 100%
	Unaged Tensile Strength	Min. 1.407 Kgf/mm ²
	Aging at 100°C for 168Hrs	Min. Elongation Retention: 50%
		Min. Tensile Strength Retention: 75%

Applications

10GBASE-T Ethernet
 1000BASE-TX Gigabit Ethernet
 ATM CB1G
 1000BASE-T Gigabit Ethernet
 100VG-AnyLAN

100BASE-TX Fast Ethernet
 10BASE-TX Ethernet
 155/622 Mbps ATM
 100 Mbps TP-PMD
 4/16 Mbps Token Ring

Electrical Performance

Dielectric Strength of Insulation		2500 V dc / 2 seconds		
Insulation Resistance Test		Min. 5000 MΩ·Km		
Conductor Resistance		Max. 9.38 Ω/100m at 20°C		
Resistance Unbalance		Max. 2%		
Capacitance Unbalance		Max. 160 pF/100m		
Mutual Capacitance		Max. 5600 pF/100m		
Impedence	64kHz	125Ω ± 20%		
	1~500MHz	100Ω ± 15%		
Attenuation & Near End Cross Talk	Frequency (MHz)	Max.Attenuation (dB/100 meters)	NEXT (dB), Min.	PSNEXT (dB), Min.
	1 MHz	2.5*	74.3*	72.3*
	10 MHz	7.1*	59.3*	57.3*
	100 MHz	23.0*	44.3*	42.3*
	200 MHz	33.1*	39.8*	37.8*
	250 MHz	37.3*	38.3*	36.3*
	300 MHz	41.1*	37.1*	35.1*
	400 MHz	51.2*	35.3*	33.3*
	500 MHz	54.3*	33.8*	31.8*

The asterisked (*) value are for information only. The minimum Next coupling loss for anypair combination at room temperature is to be greater than the value determined using the formula: $NEXT(f\text{ MHz}) \geq NEXT(0.772) - 15\text{LOG}_{10}(f\text{ MHz}/0.772)\text{dB}$

Configuration

orange 2 white/orange	green 3 white/green
blue 1 white/blue	brown 4 white/brown

