



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REV/REDRAWN PER ECN #16890	12/2/86	LASWETT
01 ₁	REVISED PER ECN 92-0010	08/21/92	<i>M.M.</i> <i>R.C.</i> 7/26/93

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions BNC MIL-STD-348A Fig. 301.1	Temperature Rating <u>-65°C to +165°C</u>
Frequency Range (GHz) <u>DC to 4</u>	OSM MIL-STD-348A Fig. 310.2	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>	Recommended Mating Torque <u>4-6 In-Lbs</u>	Shock MIL-STD-202, Method 213, Condition I
VSWR <u>1.30 Max</u> at 0.5 to 4.0 GHz	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B,
Insertion Loss (dB MAX) <u>0.2√f(GHz)</u>		Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) <u>-55, 2 to 3 GHz</u>	BNC OSM	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Insertion (Lbs Max) <u>N/A 3.0</u>	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1500</u>	Withdrawal (Oz Min) <u>N/A 1.0</u>	
Contact Resistance (Milliohms MAX)	Force to Engage/Disengage	
Center Contact <u>4.1</u>	Longitudinal	
Outer Contact <u>2.2</u>	Force (Lb Max) <u>3.0 N/A</u>	
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>	Torque (In-Lb Max) <u>2.5 2.0</u>	
I.R.(Megohms MIN) <u>5000</u>	Contact Retention	
	Axial (Lbs Min) <u>6.0</u>	
	Radial (In-Oz) <u>N/A</u>	
	Weight (Grams) <u>TBD</u>	

COMPONENT	MATERIAL	FINISH
HOUSING (OSB)	BRASS PER QQ-B-626 COMP. 360, HALF HARD	NICKEL PLATE PER QQ-N-290
HOUSING (OSM)	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY	DATE	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	FRAC.	DEC.	
± 1/64	±.005	± °	
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	CHECKED BY	DATE	AMP
	APPD BY	DATE	
USE ASS'Y PROCEDURE	LASWETT	12/2/86	
NO. AP. <u>N/A</u>	B. CLEVELAND	1/16/87	
TITLE			REV
OSB PLUG TO OSM JACK ADAPTER			01 ₁
SIZE	CODE IDENT NO.	3282-2240-00	
B	26805		
SCALE	4:1		SHEET 1 OF 1