



Metric table

Dimensions in: millimeters - inches

1 d ₁	2 d ₂ Thread VB-FP	VB-FP-H			d ₃	d ₄	h ₁	h ₂	t
20 .79	M 6	-	-	-	13 .51	7.5 .30	15 .59	7 .28	11 .43
30 1.18	M 5	M 6	M 8	-	17 .67	9 .35	24 .94	11 .43	15 .59
40 1.57	-	-	-	M 6	M 8	M 10	21 .83	13 .43	18 .71
50 1.97	-	-	-	M 8	M 10	M 12	24 .94	15 .59	18 .71
60 2.36	-	-	-	M 12	-	-	28 1.10	15 .59	25 .98
60 2.36	-	-	-	M 16	-	-	28 1.10	15 .59	25 .98
70 2.76	-	-	-	M 16	-	-	32 1.26	21 .83	25 .98

Specification

- Six-lobed knob
Phenolic plastic
 - Temperature resistant up to 300 °F (150 °C)
 - Black, shiny finish
- Tapped insert
Brass, molded-in
- RoHS compliant

Information

VB-FP and VB-FP-H six-lobed knobs offer a wide range of clamping.

see also...

- Six-Lobed Knobs VB (with Blind Tapped Insert)
- Six-Lobed Knobs VP (Solid Type, with Steel Threaded Stud)
- Six-Lobed Knobs VP-H (Hollow Type, with Steel Threaded Stud)

On request

- For certain minimum quantities, stainless steel inserts

How to order (Solid type) VB-FP-20-M6	1 Handle diameter d ₁
	2 Thread d ₂
How to order (Hollow type) VB-FP-H-40-M8	1 Handle diameter d ₁
	2 Thread d ₂