

FOC-ADAPTER:LCD/LCD-MM-ME - Fiber optic coupling



1208069

<https://www.phoenixcontact.com/us/products/1208069>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Metal, connection method: Coupling, cable outlet: straight, color: silver/matt, Ethernet

Your advantages

- High reliability with comprehensive quality assurance measures
- Optimized precision (stability) with the use of ceramic sleeves
- Versatile range of applications with an extended temperature range and various mounting options
- Suitable for use for all multimode classes
- Optimum compatibility with the FDX20 series splice boxes
- Future-proof with RoHS 2 conformity

Commercial data

Item number	1208069
Packing unit	1 pc
Minimum order quantity	6 pc
Sales key	AB15
Product key	ABNIDA
GTIN	4063151275853
Weight per piece (including packing)	11.25 g
Weight per piece (excluding packing)	11.25 g
Customs tariff number	85367000
Country of origin	CN

FOC-ADAPTER:LCD/LCD-MM-ME - Fiber optic coupling



1208069

<https://www.phoenixcontact.com/us/products/1208069>

Technical data

Product properties

Type	LC
Product type	Female insert
Sensor type	Ethernet
Number of positions	2
Connection profile	LC
Number of slots	2
Cable outlet	straight

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties

Rated surge voltage	0.8 kV
Attenuation	≤ 0.2 dB
Nominal current I_N	0.5 A
Transmission medium	FO

Connection data

Connection technology

Connection method	Coupling
-------------------	----------

Dimensions

Width	22 mm
Height	9.4 mm
Length	19.2 mm

Mechanical characteristics

Ferrule diameter	1.25 mm
------------------	---------

Material specifications

Color	silver/matt
Color of the housing part	silver
Flammability rating according to UL 94	V0
Housing surface material	metal-plated
Contact surface material	Gold
Housing material	Metal

Cable/line

Cable type	Fiberglass
External sheath, color	silver-colored

FOC-ADAPTER:LCD/LCD-MM-ME - Fiber optic coupling



1208069

<https://www.phoenixcontact.com/us/products/1208069>

Tensile strength short-term/long-term	40 N
Halogen-free	yes
Resistance to oil	yes
Flame resistance	yes

FO cable

Number of fibers	2
Fiber	50/125 µm
Fiber type	Fiberglass
Attenuation	≤ 0.15 dB

Mechanical properties

Tensile strength short-term/long-term	40 N
---------------------------------------	------

Characteristics

Attenuation	≤ 0.2 dB
-------------	----------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-55 °C ... 85 °C
Ambient temperature (assembly)	0 °C ... 50 °C
Resistance to UV radiation	yes
Resistance to oil	yes

Standards and regulations

Resistance to UV radiation	yes
Flame resistance	yes
Resistance to oil	yes

Mounting

Connection method	Coupling
-------------------	----------

FOC-ADAPTER:LCD/LCD-MM-ME - Fiber optic coupling



1208069

<https://www.phoenixcontact.com/us/products/1208069>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1208069>



EAC

Approval ID: B.01687

FOC-ADAPTER:LCD/LCD-MM-ME - Fiber optic coupling



1208069

<https://www.phoenixcontact.com/us/products/1208069>

Classifications

ECLASS

ECLASS-11.0	27440392
ECLASS-13.0	27440392
ECLASS-12.0	27440392

ETIM

ETIM 8.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

FOC-ADAPTER:LCD/LCD-MM-ME - Fiber optic coupling



1208069

<https://www.phoenixcontact.com/us/products/1208069>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com