



Main

Kategorie	Mounting accessory
Product or Component Type	Connector
Range compatibility	Spacial CRN Spacial S3D Spacial S3CM
Anwendung	Multi-purpose
Nennmaße des Gehäuses	-
Mounting Location	Between C60 rails or with any other section
Device composition	1 connector
Quantity per Set	Set of 20
Material	steel

Complementary

Surface Finish	Zinc coated
Fixing mode	By fixing element
Height	2.36 in (60 mm)
Width	2.36 in (60 mm)
Depth	2.36 in (60 mm)
Thickness	0.12 in (3 mm)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480181733
Nbr. of units in pkg.	1
Package weight(Lbs)	5.29 oz (150.0 g)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.54 in (9 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	5.31 in (13.5 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	6.61 lb(US) (3.0 kg)
Package 2 Height	3.54 in (9 cm)
Package 2 width	3.15 in (8 cm)
Package 2 Length	5.31 in (13.5 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------