

CAT-3 • CAT-3-R16 • CAT-3-R18

The CAT-3-CHUCK Rewinder Series affords the fastest loading and unloading of cores and label rolls, and is ideal for high-volume production environments, label slitting applications, or anywhere the ultimate convenience in Rewinders is desired.



CAT-3-CHUCK-220

Technical Specifications	CAT-3	CAT-3-R16	CAT-3-R18
Max Roll Diameter (in)	12 (305-mm)	16 (406-mm)	18 (457-mm)
Core Diameter (in)	3 (76-mm)		
Max Media Width (in) ¹	6 - 10 (152 - 254-mm)		
Max Roll Weight (lbs)	20 (9-kg)	32 (14.5-kg)	50 (22-kg)
Dimensions-HWD (in)	14x12x17 (355 x 305 x 432-mm)	19x16x17 (482 x 406 x 432-mm)	20x18x19 (508 x 457 x 482-mm)
Weight (lbs) ¹	28 - 30 (12.7 - 13.6-kg)	30 - 32 (13.6-kg - 14.5-kg)	34 - 36 (15.4 - 16.3-kg)
Max Speed (ips)	240 (6096-mm)	320 (8128-mm)	360 (9144-mm)
Min Speed (ips)	0.5 (13-mm)		
Max Torque (in-oz) ^{2,3}	183	228	228
Max RPM ²	388	485	
Number of Flanges	2		
Power Specifications	120 - 220VAC in, 12VAC 40W Out ¹	120 - 220VAC in, 19VDC 80W Out	
Warranty	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor		
Available Options	<ul style="list-style-type: none"> • HTO-CAT (Hi-Torque Option) • LTO-CAT (Lw-Torque Option) • ADAPT-326 (6" Core Adaptor) • FOOTSWITCH 	<ul style="list-style-type: none"> • LTO-CAT (Lw-Torque Option) • ADAPT-326 (6" Core Adaptor) • FOOTSWITCH 	<ul style="list-style-type: none"> • LTO-CAT (Lw-Torque Option) • ADAPT-326 (6" Core Adaptor) • FOOTSWITCH

1. Depends on whether you order the CHUCK, CHUCK-220, or CHUCK-10 model

2. HTO-CAT increases Max Torque to 228 in-oz, Max RPM to 485, 304 ips (7,721-mm), and Power Out to 19VDC 80W.

3. LTO-CAT decreases Torque Range to 172 - 35 in-oz.