


CRT Display, Video Output

- High Current Gain Bandwidth Product : $f_T = 400\text{MHz}$ (Typ.)
- High Collector-Base Breakdown Voltage : $V_{CBO} = -200\text{V}$
- Low Reverse Transfer Capacitance : $C_{re} = 1.7\text{pF}$ (Typ.)



PNP Epitaxial Silicon Transistor

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Ratings	Units
V_{CBO}	Collector-Base Voltage	- 200	V
V_{CEO}	Collector-Emitter Voltage	- 200	V
V_{EBO}	Emitter-Base Voltage	- 4	V
I_C	Collector Current (DC)	- 100	mA
I_{CP}	Collector Current (Pulse)	- 200	mA
P_C	Collector Dissipation ($T_a = 25^\circ\text{C}$)	1.2	W
P_C	Collector Dissipation ($T_C = 25^\circ\text{C}$)	7	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	- 55 ~ 150	$^\circ\text{C}$

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
BV_{CBO}	Collector-Base Breakdown Voltage	$I_C = - 10\mu\text{A}, I_B = 0$	- 200			V
BV_{CEO}	Collector-Emitter Breakdown Voltage	$I_C = - 1\text{mA}, R_{BE} = \infty$	- 200			V
BV_{EBO}	Emitter-Base Breakdown Voltage	$I_E = - 100\mu\text{A}, I_C = 0$	- 4			V
I_{CBO}	Collector Cut-off Current	$V_{CB} = - 150\text{V}, I_C = 0$			- 0.1	μA
I_{EBO}	Emitter Cut-off Current	$V_{BE} = - 2\text{V}, I_E = 0$			- 0.1	μA
h_{FE1} h_{FE2}	DC Current Gain	$V_{CE} = - 10\text{V}, I_C = - 10\text{mA}$ $V_{CE} = - 10\text{V}, I_C = - 60\text{mA}$	40 20		120	
$V_{CE}(\text{Sat})$	Collector-Emitter Saturation Voltage	$I_C = - 30\text{mA}, I_E = - 3\text{mA}$			- 0.8	V
$V_{BE}(\text{Sat})$	Base-Emitter Saturation Voltage	$I_C = - 30\text{mA}, I_E = - 3\text{mA}$			- 1.8	V
f_T	Current Gain Bandwidth Product	$V_{CE} = - 30\text{V}, I_C = - 30\text{mA}$		400		MHz
C_{ob}	Output Capacitance	$V_{CB} = - 30\text{V}, f = 1\text{MHz}$		2.3		pF
C_{re}	Reverse Transfer Capacitance	$V_{CB} = - 30\text{V}, f = 1\text{MHz}$		1.7		pF

*** h_{FE} Classification**

Classification	C	D
h_{FE1}	40 ~ 80	60 ~ 120

Typical Characteristics




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. Collector-Emitter Saturation Voltage




Figure 4. Base-Emitter On Voltage




Figure 5. Collector Output Capacitance




Figure 6. Reverse Capacitance

Typical Characteristics (Continued)




Figure 7. Current Gain Bandwidth Product




Figure 8. Safe Operating Area





Figure 9. Power Derating

Package Dimensions

KS A1406

TO-126



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	HiSeC™	SuperSOT™-8
Bottomless™	ISOPLANAR™	SyncFET™
CoolFET™	MICROWIRE™	TinyLogic™
CROSSVOLT™	POP™	UHC™
E ² CMOS™	PowerTrench®	VCX™
FACT™	QFET™	
FACT Quiet Series™	QS™	
FAST®	Quiet Series™	
FASTr™	SuperSOT™-3	
GTO™	SuperSOT™-6	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Fairchild Semiconductor

SEARCH | [Parametric](#) | [Cross Reference](#)

[Product Folders and](#) [Applies](#)

[find products](#)

[Home](#) >> [Find products](#) >>

[Products groups](#)

[Analog and Mixed](#)

[Signal](#)

[Discrete](#)

[Interface](#)

[Logic](#)

[Microcontrollers](#)

[Non-Volatile](#)

[Memory](#)

[Optoelectronics](#)

[Markets and](#)

[applications](#)

[New products](#)

[Product selection and](#)

[parametric search](#)

[Cross-reference](#)

[search](#)

KSA1406

PNP Epitaxial Silicon Transistor

[Contents](#)

[Features](#) | [Product status/pricing/packaging](#)

Features

CRT Display, Video Output

- High Current Gain Bandwidth Product: $f_T=400\text{MHz}$ (Typ.)
- High Collector-Base Breakdown Voltage: $V_{CBO}=-200\text{V}$
- Low Reverse Transfer Capacitance: $C_{re}=1.7\text{pF}$ (Typ.)

[Datasheet](#)

[Download this datasheet](#)

[PDF](#)

[e-mail this datasheet](#)

[\[E-\]](#)

This page

[Print version](#)

[Related Links](#)

[Request samples](#)

[How to order products](#)

[Product Change Notices \(PCNs\)](#)

[Support](#)

[Distributor and field sales representatives](#)

[Quality and reliability](#)

[Design tools](#)

[technical information](#)

[buy products](#)

[technical support](#)

[my Fairchild](#)

[company](#)

[back to top](#)

[Product status/pricing/packaging](#)

Product	Product status	Pricing*	Package type	Leads	Packing method
KSA1406CSTU	Full Production	\$0.193	TO-126	3	RAIL

* 1,000 piece Budgetary Pricing

[back to top](#)

[Home](#) | [Find products](#) | [Technical information](#) | [Buy products](#) | [Support](#) | [Company](#) | [Contact us](#) | [Site index](#) | [Privacy policy](#)

© Copyright 2002 Fairchild Semiconductor