



SPECIFICATION
MATERIALS:
 HOUSING & INSERT: PBT YELLOW
 COUPLING: BRASS-NICKEL PLATED
 O-RING: VITON
ELECTRICAL:
 VOLTAGE: 10-30VDC
 CURRENT RATING: 4A PER PORT, 12 AMPS MAX.
 PROTECTION CLASS: IP67
 OPERATING TEMPERATURE: -5°C to +90°C

NOTES:
 FIXING HOLES TO SUIT M4 SCREWS

MATERIAL NUMBER	OLD PART NUMBER	FINISHED LENGTH	CABLE JACKET MATERIAL
1201140191	BTY412N-FBP-003	0.3M ± 25MM	PUR

DESCRIPTION EC NO: WEU2010-0450 DRWN: REISSNER 2010/03/19 CH'KD: FP APPR: NSTAUDIG 2010/03/23	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
		mm	INCH	MM ONLY	2:1	METRIC	
	$\nabla = 0$ $\nabla \text{C} = 0$	4 PLACES ±---	±---	DRAWN BY	DATE	MICRO-CHANGE MPIS 4 PORT TOP MOUNT 19POLE MINI-CHANGE	
		3 PLACES ±---	±---	REISSNER	2010/03/19		
		2 PLACES ±---	±---	CHECKED BY	DATE	MOLEX INCORPORATED	
	1 PLACE ±0.3	±---	NS	2010/03/19			
	ANGULAR ± --- °		APPROVED BY	DATE	DOCUMENT NO.	SHEET NO.	
			NSTAUDIG	2010/03/23	SD-120114-067	1 OF 1	
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
1	REV	SIZE	A3				