



ELECTRO-OPTICAL CHARACTERISTICS		T <sub>a</sub> =25°C		I <sub>f</sub> =20mA	
PARAMETER	MIN	TYP	MAX	UNITS	
OPERATING VOLTAGE	90		115	V	
STARTING VOLTAGE (AC)			95	V	
STARTING VOLTAGE (DC)			135	V	
OPERATING CURRENT		1.7		mA	
LIGHT OUTPUT		65		mLM	
LIFE HOURS		20,000		HOURS	

NOTES

- EXTERNAL RESISTOR VALUE 33k OHMS
- LEAD LENGTH 25mm MIN.
- LEAD SPACING 2mm TYP
- MINIMUM VALUE IS NOT GUARANTEED.
- LEAD FINISH IS TO BE SHINY TIN COATING.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION

UNCONTROLLED DOCUMENT



290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
FAX: +1.847.359.6538  
WEB: WWW.LUMEX.COM

NEON LAMP, T-4mm HIGH BRIGHTNESS, TIN COATING.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	08.24.11	DRAWN BY:	AB
PAGE:	1 OF 1	CHKD BY:	KF
SCALE:	NTS	APRVD BY:	SS
UNIT:	mm [INCH]		Ⓟ