

Printed-circuit board connector - MSTB 2,5/ 7-G-5,08 PA(1,3,5,7) - 1723955

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 12 A, Number of positions: 7, Pitch: 5.08 mm, Color: green, Contact surface: Tin, Mounting: Wave soldering



Key Commercial Data

| | |
|------------------------|----------|
| Packing unit | 1 STK |
| Minimum order quantity | 50 STK |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Environmental Product Compliance

| | |
|------------|--|
| China RoHS | No hazardous substances above threshold values |
|------------|--|

Dimensions

| | |
|--------------------------|----------|
| Pitch | 5.08 mm |
| Dimension a | 30.48 mm |
| Constructional height | 9 mm |
| Length of the solder pin | 3.5 mm |

General

| | |
|----------------------------------|---------------|
| Range of articles | MSTB 2,5/..-G |
| Rated voltage (III/3) | 250 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 12 A |
| Color | green |
| Number of positions | 7 |

Standards and Regulations

| | |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
| | CSA |

Printed-circuit board connector - MSTB 2,5/ 7-G-5,08 PA(1,3,5,7) - 1723955

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals


Approvals

Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / IECCEB Scheme / EAC / cULus Recognized / EAC

Ex Approvals


Approval details


| | | |
|---|------|------|
| CSA  http://www.csagroup.org/us/en/services/testing-and-certification/certified-product-listing-13631 | | |
| | B | D |
| Nominal current I _N | 15 A | 10 A |

Printed-circuit board connector - MSTB 2,5/ 7-G-5,08 PA(1,3,5,7) - 1723955

Approvals

| | B | D |
|--------------------|-------|-------|
| Nominal voltage UN | 300 V | 300 V |

| | |
|--|-------|
| VDE Gutachten mit Fertigungsüberwachung  http://www.vde.de 40004701 | |
| Nominal current IN | 12 A |
| Nominal voltage UN | 250 V |

| | |
|--|-------|
| IECEE CB Scheme  http://www.iecee.org/ DE1-56062-B1B2 | |
| Nominal current IN | 12 A |
| Nominal voltage UN | 250 V |

| |
|-------------------|
| EAC EAC-Zulassung |
|-------------------|

| cULus Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-19931011 | | |
|--|-------|-------|
| | B | D |
| Nominal current IN | 15 A | 15 A |
| Nominal voltage UN | 300 V | 150 V |

| |
|-------------|
| EAC B.01742 |
|-------------|