


## Main Product Characteristics

BV <sub>DSS</sub>	100V
R <sub>DS(ON)</sub>	38mΩ
I <sub>D</sub>	16A



PPAK 3x3



Schematic Diagram

## Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery



## Description

The GSFN0988 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supplies and a wide variety of other applications.

## Absolute Maximum Ratings (T<sub>C</sub>=25°C unless otherwise specified)

Parameter	Symbol	Max.	Unit
Drain-Source Voltage	V <sub>DS</sub>	100	V
Gate-Source Voltage	V <sub>GS</sub>	+20/-12	V
Drain Current-Continuous (T <sub>C</sub> =25°C)	I <sub>D</sub>	16	A
Drain Current-Continuous (T <sub>C</sub> =100°C)		10	
Drain Current-Pulsed <sup>1</sup>	I <sub>DM</sub>	64	A
Single Pulse Avalanche Energy <sup>2</sup>	E <sub>AS</sub>	34	mJ
Single Pulse Avalanche Current <sup>2</sup>	I <sub>AS</sub>	26	A
Power Dissipation (T <sub>C</sub> =25°C)	P <sub>D</sub>	32.5	W
Power Dissipation - Derate above 25°C		0.26	W/°C
Thermal Resistance, Junction-to-Ambient	R <sub>θJA</sub>	62	°C/W
Thermal Resistance, Junction-to-Case	R <sub>θJC</sub>	3.85	°C/W
Operating Junction Temperature Range	T <sub>J</sub>	-55 To +150	°C
Storage Temperature Range	T <sub>STG</sub>	-55 To +150	°C

**Electrical Characteristics** ( $T_J=25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
<b>On / Off Characteristics</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	100	-	-	V
Drain-Source Leakage Current	$I_{\text{DSS}}$	$V_{\text{DS}}=100\text{V}, V_{\text{GS}}=0\text{V}, T_J=25^\circ\text{C}$	-	-	1	$\mu\text{A}$
		$V_{\text{DS}}=80\text{V}, V_{\text{GS}}=0\text{V}, T_J=125^\circ\text{C}$	-	-	10	$\mu\text{A}$
Gate-Source Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}}=20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	100	nA
Static Drain-Source On-Resistance <sup>3</sup>	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=10\text{A}$	-	32	38	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_{\text{D}}=8\text{A}$	-	49	63	
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}, I_{\text{D}}=250\mu\text{A}$	1.0	1.6	2.5	V
Forward Transconductance	$g_{\text{fs}}$	$V_{\text{DS}}=10\text{V}, I_{\text{S}}=3\text{A}$	-	5	-	S
<b>Dynamic and Switching Characteristics</b>						
Total Gate Charge <sup>3,4</sup>	$Q_g$	$V_{\text{DS}}=50\text{V}, I_{\text{D}}=10\text{A}$ $V_{\text{GS}}=10\text{V}$	-	8	12	nC
Gate-Source Charge <sup>3,4</sup>	$Q_{\text{gs}}$		-	2.1	3.5	
Gate-Drain Charge <sup>3,4</sup>	$Q_{\text{gd}}$		-	2.3	4	
Turn-On Delay Time <sup>3,4</sup>	$t_{\text{d}(\text{on})}$	$V_{\text{DD}}=50\text{V}, R_{\text{G}}=3.3\Omega$ $V_{\text{GS}}=10\text{V}, I_{\text{D}}=1\text{A}$	-	7.4	15	nS
Rise Time <sup>3,4</sup>	$t_r$		-	12	24	
Turn-Off Delay Time <sup>3,4</sup>	$t_{\text{d}(\text{off})}$		-	23	46	
Fall Time <sup>3,4</sup>	$t_f$		-	16	32	
Input Capacitance	$C_{\text{iss}}$	$V_{\text{DS}}=20\text{V}, V_{\text{GS}}=0\text{V}, F=1\text{MHz}$	-	553	740	pF
Output Capacitance	$C_{\text{oss}}$		-	181	460	
Reverse Transfer Capacitance	$C_{\text{rss}}$		-	30	20	
Gate Resistance	$R_g$	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, F=1\text{MHz}$	-	0.8	-	$\Omega$
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
Continuous Source Current	$I_s$	$V_G=V_D=0\text{V},$ Force Current	-	-	16	A
Pulsed Source Current	$I_{\text{SM}}$		-	-	32	A
Diode Forward Voltage	$V_{\text{SD}}$	$V_{\text{GS}}=0\text{V}, I_s=1\text{A}, T_J=25^\circ\text{C}$	-	-	1	V
Reverse Recovery Time	$t_{\text{rr}}$	$V_{\text{GS}}=0\text{V}, I_s=10\text{A}$ $dI/dt=100\text{A}/\mu\text{s}, T_J=25^\circ\text{C}$	-	30	-	nS
Reverse Recovery Charge	$Q_{\text{rr}}$		-	24	-	nC

Note:

- Repetitive rating: Pulsed width limited by maximum junction temperature.
- $V_{\text{DD}}=50\text{V}, V_{\text{GS}}=10\text{V}, L=0.1\text{mH}, I_{\text{AS}}=26\text{A}, R_{\text{G}}=25\Omega$ , starting  $T_J=25^\circ\text{C}$ .
- Pulse test: pulse width  $\leqslant 300\text{us}$ , duty cycle  $\leqslant 2\%$ .
- Essentially independent of operating temperature.

## Typical Electrical and Thermal Characteristic Curves




Figure 1. Continuous Drain Current vs. T<sub>c</sub>




Figure 2. Normalized R<sub>DS(on)</sub> vs. T<sub>j</sub>




Figure 3. Normalized V<sub>th</sub> vs. T<sub>j</sub>




Figure 4. Gate Charge Characteristics




Figure 5. Normalized Transient Response




Figure 6. Maximum Safe Operation Area

### Typical Electrical and Thermal Characteristic Curves




Figure 7. Switching Time Waveform

$$EAS = \frac{1}{2} L \times I_{AS}^2 \times \frac{BV_{DSS}}{BV_{DSS} - V_{DD}}$$





Figure 8. EAS Waveform

### Package Outline Dimensions PPAK3x3



Symbol	Dimensions In Millimeters		Dimensions in Inches	
	MIN	MAX	MIN	MAX
A	0.700	0.900	0.028	0.035
b	0.240	0.350	0.009	0.014
c	0.100	0.250	0.004	0.010
D	3.050	3.450	0.120	0.136
D1	2.900	3.200	0.114	0.126
D2	1.350	1.850	0.053	0.073
E	3.000	3.400	0.118	0.134
E1	2.900	3.250	0.114	0.128
E2	2.350	2.600	0.093	0.102
e	0.650 BSC		0.026 BSC	
H	0.300	0.500	0.012	0.020
L	0.300	0.500	0.012	0.020
L1	0.070	0.200	0.003	0.008
θ	0°	12°	0°	12°

### Order Information

Device	Package	Marking	Carrier	Reel QTY
GSFN0988	PPAK3x3	DC0988	Tape & Reel	3,000pcs