

PULS MiniLine:  
practical, versatile and reliable like  
the SilverLine – yet small like no other:

**PULS**

CE

UL US LISTED

CB  
scheme



Data sheet

# MiniLine with plug-in screw terminals



- 24-28 V DC/50 W output power
- 100-240 V Wide Range Input (85-264 V AC permitted)
- DCok output
- PULS Overload Design™ (does not switch off at overload but delivers up to 1.5 times nominal current)
- with load sharing for reliable parallel operation
- NEC Class 2 Power Supply

PULS GmbH, Arabellastrasse 15, D-81925 Munich  
Tel. +49.(0)89.9278-244, Fax: +49.(0)89.9278-199  
sales@puls-power.com, <http://www.puls-power.com>

**Mini is more.**

## ◆ Technical Data ML50.111

### ◆ Input

Input voltage	AC100-240V (Wide Range), 47...63 Hz Admiss. limits: AC 85...264V (DC 85...375V)
Input current	<1.0A (@ AC 100V <sub>in</sub> , 50W P <sub>out</sub> ) <0.6A (@ 196 V AC <sub>in</sub> , 50W P <sub>out</sub> )
External Fusing	Not required, unit provides internal fuse (T3AH, not accessible)
Transient immunity	Transient resistance acc. to VDE 0160 / W2 (750V / 1.3ms), over entire load range
Hold-up time (see diagram below)	>171ms @ AC 230V, 24V / 2.1A >97ms @ AC 196V, 24V / 2.1A >17ms @ AC 100V, 24V / 2.1A

### ◆ Efficiency, Reliability

Efficiency	typ. 88.5% (AC 230V, 24V / 2.1A) (see also diagram below)
Losses	typ. 6.8W (AC 230V, 24V / 2.1A)
MTBF (Reliability)	ca. 600.000 h acc. to Siemensnorm SN 29500 (24V/2.1A, AC 230V, T <sub>amb</sub> = +40°C)

Prior to shipment, every unit undergoes the following tests in order to isolate any defective units which might suffer an early failure:

- Run-in / burn-in (Full load, T<sub>amb</sub> = +60°C, on/off cycle)
- Functional test (100 %)

### ◆ Construction, Mechanics, Installation

Robust plastic housing (US Patent No. D442, 9235), fine ventilation grid on three housing sides to keep out small parts (e.g. screws), IP20

Dimensions and weight

- W x H x D 45mm x 75mm x 91mm (+ DIN rail)  
Depth incl. connectors: 98mm (+ DIN rail)
- Weight 240g

Mounting orientation  (cf. 'Output')

Ventilation/Cooling Normal convection, no fan required

- Free space f. cooling recom'd.: 25mm on sides with ventilation grid

Easy snap-on mounting onto the DIN-rail (TS35/7,5 or TS35/15).

Unit sits safely and firmly on the rail; no tools required even to remove

Connection by plug connectors, 2 terminals/output; mating connectors enclosed

Connector size range – input:

- flexible/solid cable 0.5 - 2.5mm<sup>2</sup> (22-12 AWG)
- Wire strip length Ferrules admissible, 7mm recommended

Connector size range – output:

- flexible cable 0.3 - 2.5mm<sup>2</sup> (28-12 AWG)
- solid cable 0.3 - 4mm<sup>2</sup> (28-12 AWG)
- Wire strip length Ferrules admissible, 6mm recommended

Design details – for your advantage:

- Standard plugs, meet various connector families (e.g. CombiCon)
- Plugs allow measurement access

### ◆ Output (incl. Logic)

Output voltage	DV 24-28V, adj. by front panel potentiometer
• preset	24V ±0.5% @ 2.1A (25V at no load, see 'Parallel operation')
Voltage regulation	stat. ±2.5% V <sub>out</sub> (see 'Parallel operation') dyn. ±2% V <sub>out</sub> overall
Ripple/Noise	<50mV <sub>pp</sub> (20MHz bandw., 50Ω measur.)
Overvoltage prot. (OVP)	<40V
Output noise suppression	Radiated EMI values below EN 61000-6-3, even when using long (>2m), unscreened output cables
Rated continuous loading	up to 2.1A @ 24V / up to 1.8A @ 28V depending on built-in orientation, V <sub>in</sub> and T <sub>amb</sub> (convection cooling); for details see derating diagram below
Overload behaviour	<b>PULS Overload Design™:</b> No switch-off at overload/short-circuit, instead: up to 1.5 · I <sub>rated</sub> . So you need no oversizing to start awkward loads.
Protection	Unit is protected against (also permanent) short-circuit, overload and open-circuit
Derating	see diagram below
Parallel operation	Yes; load sharing by inclined characteristic curve (ΔV = -1V between I <sub>out</sub> = 0A and I <sub>out</sub> = I <sub>rated</sub> )
Power back immunity	35V
Operation indicator	Green LED (DC OK), threshold: V <sub>out</sub> = 20V
DC OK output	To feed a 24V relay (R <sub>coil</sub> > 700Ω). Relay operates, if output voltage exceeds threshold value Free-wheeling diode for relay is included in the power supply unit
• Threshold	V <sub>out</sub> = 20V ±4%

### ◆ Environmental Data, EMC, Safety

Ambient temperature range (measured 25mm below unit)	
• storage, transport	-25°C ... +85°C
• operation	-10°C ... +70°C (for derating see diagram below)
Humidity	max. 95% (without condensation)
Electromagnetic emissions (EME)	EN 61000-6-3 (includes EN 61000-6-4) Class B (EN 55011, EN 55022)
Electromagnetic immunity (EMI)	EN 61000-6-2 (includes EN 61000-6-1)
Safe low voltage:	SELV (EN60950, VDE0100/T.410), PELV (EN50178)
Prot. class/degree:	Class I (EN60950) / IP20 (EN60529)


The PSU complies with all major **safety approvals** for EU (EN 60950, EN 60204-1, EN 50178), USA (UL 60950, E137006, UL508 LISTED, E198865), Canada (CAN/CSA-C22.2 No 60950 [CUR], CAN/CSA-C22.2 No. 14 [CUL]), CB Scheme (IEC 60950).

Further design details – for your advantage:


- All terminals are easy to reach as mounted on the front panel.
- Input and output are strictly apart from each other (below/above) and have different wire access (90°/270° wiring), so cannot be mixed up

### ◆ Diagrams


**Output characteristic V<sub>out</sub>/I<sub>out</sub> (min.)**



**Efficiency (@ V<sub>out</sub> = 24V, typ.)**



**Derating of output power**



**Hold-up time with ACin (@ V<sub>out</sub> = 24V, typ. + min.)**

