# swissbit®

Product Fact Sheet

Industrial USB Flash Drive Module

U-48 Series USB 2.0 High-Speed, pSLC

Commercial and Industrial Temperature Grade

Date: Revision: January 26, 2023 1.01



## swissbit®

### **Product Summary**

- Capacities: 8 GBytes, 16 GBytes
- Form Factor:
  - USB 2.0 solid state flash drive for internal 10-pin USB connector terminal (26.65mm x 36.8mm)
  - o 2.54mm or 2.00mm connector with keyed pin9
- Compliance: USB 2.0 High-Speed specification compatible (backward compliance with USB 1.1)
- Performance:
  - Read Performance: Sequential Read up to 42 MBytes/s, Random Read IOPS up to 2,600
  - Write Performance: Sequential Write up to 38 MBytes/s, Random Write IOPS up to 2,000
- Operating Temperature Range:
  - $\circ$   $\,$  Commercial: o °C to 70 °C  $\,$
  - Industrial: -40 °C to 85 °C
- Storage Temperature Range: -40 °C to 85 °C
- **Operating Voltage:** 3.3V ±5% or 5V ± 10%
- Data Retention: 10 Years @ Life Begin; 1 Year @ Life End
- Endurance in TeraBytes Written (TBW):
  - Enterprise Workload: up to 102
- Shock/Vibration: 1,500 g / 50 g
- High-Performance 32-Bit Processor with Integrated, Parallel Flash Interface Engine:
  - Triple-Level Cell (TLC) 3D NAND Flash in pSLC mode
    - Hardware BCH Code ECC (6obit correction per 1024 Bytes)
- High Reliability:
  - Mean Time Between Failure (MTBF): > 3,000,000 hours @ 25°C
  - $\circ$  Data Reliability: < 1 non-recoverable error per 10<sup>16</sup> bits read

### **Product Features**

- Subpage based Flash management for increased endurance & random performance
- Optimized FW algorithms especially for high read access and long data retention applications
  - Proven power fail management for highest reliability
  - Near Miss ECC technology
  - Read Disturb Management
  - Wear Leveling technology
  - Data Care Management
- Detailed S.M.A.R.T. support and extended vendor information
- LED for operation indication
- In-field firmware update
- Swissbit Life Time Monitoring (SBLTM) tool and SDK for SBLTM (on request)
- Controlled BOM & PCN process
- Customized options like registers, removable device, connector options, write protect switch, grounded mounting hole, densities, uploads, label, etc.

#### Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

Swissbit AG Industriestrasse 4 CH-9552 Bronschhofen Switzerland

TLP: Swissbit public

**Revision: 1.01** Template: Doc-4991 File: U-48\_fact\_sheet\_Rev101 Page 2 of 2