

Female connector - V-RC/TGUM 11/KVD 11/LBL 12 - 1000041

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



M23 socket, 12-pos., straight, freely configurable, with solder connection, for external cable diameter of 8 mm ... 12 mm

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 128 (PC-2009)
GTIN	 4 017918 399832
Custom tariff number	85366990
Country of origin	GERMANY

Technical data

General data

Rated voltage	150 V
Total rated current	8 A (with 1 mm ² conductor cross section)
Number of positions	12
Degree of protection	IP65/67
Inflammability class according to UL 94	V0
Ambient temperature (operation)	-20 °C ... 80 °C

Master cable data

Connection method	M23 screw locking
Conductor cross section max. (signal)	1 mm ²
Conductor cross section max. (energy)	1 mm ²
External cable diameter min.	8 mm
External cable diameter max.	12 mm

Insulation material

Housing material	GD-Zn
Housing surface material	Nickel-plated
Contact material	CuZn
Contact surface material	Gold-plated
Contact carrier material	PBT

Female connector - V-RC/TGUM 11/KVD 11/LBL 12 - 1000041

Technical data

Connection assignment

Slot/position = pin = conductor color	1 / 4 (A) = 1 = WH
Slot/position = pin = conductor color	2 / 4 (A) = 2 = GN
Slot/position = pin = conductor color	3 / 4 (A) = 3 = YE
Slot/position = pin = conductor color	4 / 4 (A) = 4 = GY
Slot/position = pin = conductor color	5 / 4 (A) = 5 = PK
Slot/position = pin = conductor color	6 / 4 (A) = 6 = RD
Slot/position = pin = conductor color	7 / 4 (A) = 7 = BK
Slot/position = pin = conductor color	8 / 4 (A) = 8 = VT
Slot/position = pin = conductor color	1-8 / 1 (+ 120 V) = 11 = BN
Slot/position = pin = conductor color	1-8 / 3 (0 V) = 9+10 = BU
Slot/position = pin = conductor color	1-8 / 5 (PE) = 12 = GN/YE

Classifications

eclass

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27061801

etim

ETIM 2.0	EC000437
ETIM 3.0	EC001121
ETIM 4.0	EC001121

unspsc

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Accessories

Accessories

Pipe spanner - PLUSCON-RCS - 1665062



Special pipe spanner, tool for mounting the M23 connector housing (with assembly), for coupling and sleeve housing

Female connector - V-RC/TGUM 11/KVD 11/LBL 12 - 1000041

Drawings

Dimensioned drawing

Schematic diagram



Pin assignment M23 socket, 12-pos., female side view