



Part Number:	MU064602-2	
	DRAWN	2/28/2017
	CJ	
Description:	CHECKED	2/28/2017
	P.D.	
	APPROVED	2/28/2017
	C.E.	
<small>This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com</small>		


Top View



Side View



Bottom View



Items	Specifications	Conditions
Directivity	Unidirectional	
Sensitivity	-46 ± 4	dB
Frequency Range	100 ~ 10,000	Hz
Rated Voltage	2	V
Voltage Range	1 ~ 10	V
Output Impedance	2,200	Ω
Max. Rated Current	0.5	mA
Storage Temperature	-20 ~ +60	°C
Operating Temperature	-10 ~ +50	°C
Signal to Noise Ratio	>55	dB
Mount Type	Flush Mount	
Connection Method	Solder Pads	

REVISION HISTORY

REV	DESCRIPTION	DATE	APPROVED
1	Released from Engineering Update to new template, correct to 4 holes	10/21/2013 2/28/2017	J.S. C.E.

NOTES

- 1) All dimensions are in mm unless otherwise noted
- 2) All tolerances are ± 0.5 mm unless otherwise noted
- 3) All parts meet RoHS
- 4) Subject to change or redrawn without notice