



specifications

Consumption	Lumen Output	CRI	Efficacy	SP	Ambient Temp (F)	L70 hours	Beam Angle	Material	THD	Standard Finish	IP Rating	Dimmable
9 W	750	> 80	83 lm / W	> 0.95	-4°- 104°	50,000	120°	durable aluminum body	< 30%	white	20 damp location	yes triac

select your downlight fixture

Part Number	Color Temp	Voltage	Included Accessories
GI-4RLK-CCT60-ES4	 selectable	⚡ 120 V	spring clips

Select your accessories*

4" Trim Accessories Part Number
<input type="radio"/> Matte Black <input type="radio"/> Satin Nickel
 GI-ACC-4RLKB
 GI-ACC-4RLKN

*optional

other specifications

Dimensions	Warranty	Weight	Case QTY
light: 4.72" (D) x 4.13 (H)" driver: 3" (D) x 1" (H) x 3.5" (W)	6 years	0.72 lbs	40 pcs



- Features**
- ▶ Selectable (dip switch) color temperature allows you to choose having 3000K, 4000K or 5000K
 - ▶ Optional trims in matte black or satin nickel finish
 - ▶ Aluminum junction box included

Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.

