



SS Stainless Steel

- 3 Type**
- E** With tapped blind bore
 - D** With tapped through bore

Specification

- Five-lobed knob
Plastic
Duroplast (Phenolic PF)
- Temperature resistant up to 203 °F (110 °C)
- Black, shiny finish
- **EN 5337**
Tapped insert
- Brass
- Steel (inch threads with $d_1 = 2.36''-3.35''$)
- **EN 5337.5**
Stainless steel AISI 303
- *Plastic Characteristics* → page 2135
- *Stainless Steel Characteristics* → page 2143
- **RoHS compliant**

On request

- Plain blind bore

Information

EN 5337 and EN 5337.5 five-lobed knobs, which offer the fingers a secure grip, are solid, so that there are no cavities where unhealthy residues may be deposited.
Resistant to solvents, oils, grease and other chemical agents.

see also...

- *Five-Lobed Knobs EN 5337.2 (Technopolymer Plastic)* → page 600
- *Solid Five-Lobed Knobs EN 5337.4 (Technopolymer Plastic)* → page 606

<p>How to order (Metric, brass / steel insert)</p> <p style="text-align: center;">1 2 3</p> <p>EN5337-50-M10-D</p>	<p>1 Handle diameter d_1</p> <p>2 Thread d_2</p> <p>3 Type</p>
<p>How to order (Inch, stainless steel insert)</p> <p style="text-align: center;">1 2 3</p> <p>EN5337.5-40-5/16X18-E</p>	<p>1 Handle diameter d_1</p> <p>2 Thread d_2</p> <p>3 Type</p>

Inch table

Dimensions in: inches - *millimeters*

1 d₁	2 d₂ Thread EN 5337		EN 5337.5 Type E	d₄	h₁ +0.04	h₂ +0.04	t₁ min.
	Type E	Type E					
1.26 32	1/4 x 20	-	1/4 x 20	0.75 19	0.91 23	0.43 11	0.47 12
1.57 40	1/4 x 20	5/16 x 18	5/16 x 18	0.83 21	1.06 27	0.47 12	0.51 13
1.97 50	5/16 x 18	3/8 x 16	3/8 x 16	0.98 25	1.30 33	0.55 14	0.67 17
2.36 60	3/8 x 16*	1/2 x 13*	-	1.06 27	1.46 37	0.67 17	0.79 20
2.76 70	1/2 x 13*	-	-	1.18 30	1.73 44	0.79 20	0.79 20
3.35 85	5/8 x 11*	-	-	1.38 35	2.13 54	1.18 30	0.87 22

Metric table

Dimensions in: millimeters - *inches*

1 d₁	2 d₂ Thread EN 5337				d₃	d₄	h₁ +1	h₂ +1	h₃	t₁ min.	t₂
	Type E	Type D	Type E	Type E							
32 1.26	M 6	-	-	M 6	-	19 0.75	23 0.91	11 0.43	-	12 0.47	-
40 1.57	M 6	M 8	M 8	M 8	14 0.55	21 0.83	27 1.06	12 0.47	1.5 0.06	13 0.51	18 0.71
50 1.97	M 8	M 10	M 10	M 10	16 0.63	25 0.98	33 1.30	14 0.55	1.5 0.06	17 0.67	22 0.87
60 2.36	M 10	M 12	M 12	M 12	17 0.67	27 1.06	37 1.46	17 0.67	1.5 0.06	20 0.79	26 1.02
70 2.76	M 12	-	M 12	-	17 0.67	30 1.18	44 1.73	20 0.79	1.5 0.06	20 0.79	26 1.02
85 3.35	M 16	-	M 16	-	24 0.94	35 1.38	54 2.13	30 1.18	2 0.08	22 0.87	35 1.38

*These sizes have a steel tapped insert

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

