

#### General ordering data

Order No.	0590280000
Part designation	DK 4QV/32 BL
Version	Feed-through terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, blue, TS 32
EAN	4008190038762
Qty.	100 pc(s).

#### Product notes

Note, technical data	With twin ferrules ZH 0.5 to ZH 2.5, rated voltage is 690 V.
----------------------	---

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	SIRA02ATEX3316U
Download English	SIRA02ATEX3316U_e.pdf
IECEX Certificate of Conformity	IECEXSIR05.0041U
Download	IECEXSIR05.0041U_e.pdf
ATEX voltage	275 V
ATEX current	28 A
ATEX conductor cross-section	4 mm <sup>2</sup>
IECEX voltage	275 V
IECEX current	28 A
IECEX conductor cross-section	4 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG- Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

Colour of insulating material	blue
Connection direction	on side
End plate required	Yes
Installation advice	TS 32
Insulating material	PA 66
Levels cross-connected internally	Yes
No. of identical terminals	1
No. of levels	2
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Type of connection	Screwed
Type of mounting	Clamped
UL 94 flammability rating of insulation material	V2
Version	Double terminal

#### CSA rating data

Voltage (CSA)	300 V
CSA current	10 A
Min. cross-section (CSA)	AWG 26

#### CSA rating data

Max. cross-section (CSA)	AWG 12
--------------------------	--------

#### Conductors for clamping (rated connection)

Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	6 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	4
Stripping length	8 mm
Clamping screw	M 3
Blade size	0.6 x 3.5 mm
Tightening torque range	0.5...0.8 Nm
Torque level with DMS electric screwdriver	2
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	6 mm <sup>2</sup>
Stranded, min.	0.5 mm <sup>2</sup>
Stranded, max.	4 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	4 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.13 mm <sup>2</sup>
AWG conductor size, max.	3.31 mm <sup>2</sup>

#### Dimensions

Width	6 mm
Height of lowest version	59.5 mm
Length	54 mm
Weight	14.87 g
TS 32 offset	10 mm

#### Disconnect terminals

Torque level with DMS electric screwdriver	2
--	---

#### Rating data

Rated cross-section	4 mm <sup>2</sup>
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	32 A
Standards	IEC 60947-7-1
Current with max. conductor	41 A

#### Rating data

Pollution severity 3

#### UL rating data

Voltage (UL) 300 V

Current (UL) 27 A

Min. cross-section (UL) AWG 22

Max. cross-section (UL) AWG 12

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

#### Similar products

Order No.	Part designation	Version
0355460000	DK 4	Feed-through terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 32
0355480000	DK 4 BL	Feed-through terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, blue, TS 32
0590060000	DK 4Q/32	Feed-through terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 32
0590080000	DK 4Q/32 BL	Feed-through terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, blue, TS 32
0590260000	DK 4QV/32	Feed-through terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 32