



NOTES:

- PRODUCT SPEC.: 108-5302, 114-5142
- APPLICABLE CONTACT P/N
TAB CONTACT: 175150-□ (*20-#16AWG)
175149-□ (*26-#22AWG)
- MATING CONN, P/N
PLUG HSG: 176276-□
REC CONTACT: 175152-□ (*20-#16AWG)
175151-□ (*26-#22AWG)
- INSTRUCTION SHEET: IS-503J

- 注:
- 適用製品規格: 108-5302
 - 適用コンタクト型番
タブ・コンタクト: 175150-□ (*20-#16AWG)
175149-□ (*26-#22AWG)
 - 嵌合相手側製品型番
プラグ・ハウジング: 176276-□
リセ・コンタクト: 175152-□ (*20-#16AWG)
175151-□ (*26-#22AWG)
 - 取扱説明書: IS-503J

回路番号 (CIRCUIT No.)	色 (COLOR)	極数 (Pos.)	型番 (P/N)
Discontinued	黒 (BLACK)	9	176287-9
Development	青 (BLUE)	↑	↑ -6
	黄 (YELLOW)		-4
	赤 (RED)	↓	↓ -2
	自然色 (NATURAL)	9	176287-1
ハウジング色調 (HOUSING COLOR)	極数 (Pos.)		型番 (P/N)

© 18 株式会社 AMP		© 19 BY AMP (Japan) LTD.		AMP 東京、日本 Tokyo, Japan	
完全電線許容範囲 (WIRE RANGE) mm ² (AWG)		絶縁外径 (INSULATION DIA.) mm		名称 (NAME) AMPユニバーサルパワーコネクタ 9極 3.96mmピッチ キャップ・ハウジング (3列タイプ) AMP UNIVERSAL POWER CONN. 3.96mm PITCH CAP HOUSING 9 Pos (TPL ROW)	
C	REVISED PER ECR-22-133029	M.G.	D.Z.	14OCT 2022	
B	改訂 J-12865	M.S.	Y.N.	10/13 '89	
A	改訂 J-12193	Y.N.	M.S.	10/13 '89	
O	作成 J-12119	M.S.	Y.F.	10/13 '89	
LTR	変更 (REVISION RECORD)	DR	CHK	DATE	
材料 (MATERIAL) S/6 ナイロン (UL94V-0) S/6 NYLON (UL94V-0)		仕上 (FINISH)		DR. Y. NARISAWA 11/19 '90 DE. M. Shide 1/9 '90 CHK. Y. Narisawa 1/9 '90 APP. J. Oono 1/9 '90	
一般公差 10mm以下: ±0.2 10mm以上 30mm以下: ±0.25 30mm以上 100mm以下: ±0.3 角 度: ±3°		SIZE	LOC	番号 (No.) A3 J C-176287	
尺度 (SCALE)		REV.	SHEET C 1 OF 1		