

2404160

https://www.phoenixcontact.com/us/products/2404160

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Emalytics Supervisor license for an additional 1250 data points

Commercial data

Item number	2404160
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DR18
Product key	DRHBAA
GTIN	4055626349121
Weight per piece (including packing)	0.001 MGM
Weight per piece (excluding packing)	0.001 MGM
Customs tariff number	49119900
Country of origin	US



2404160

https://www.phoenixcontact.com/us/products/2404160

Technical data

Product properties

Product type	Building management system
Area of application	Building technology
ystem properties	
Type of software	On-premise
Intended use for the software	Automation
	Engineering
License information	
Type of license	Runtime license
	Upgrade license
License duration	nicht relevant
Functionality	
Integrated function	Analysis
	Data acquisition
	Diagnostics
	Startup
	Communication
	Configuration
	Project planning
	Simulation
Target system	Server
Supported controllers	ILC 2050 BI
Number of data points (on-premise)	1250
Number of clients	nicht relevant
System requirements	
Languages supported	German, English
Screen resolution	1024 x 768 pixel(s) ,or higher



2404160

https://www.phoenixcontact.com/us/products/2404160

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27242590
ECLASS-12.0	27242590
ECLASS-13.0	27242590
ETIM	
ETIM 8.0	EC001435
UNSPSC	

43233600



2404160

https://www.phoenixcontact.com/us/products/2404160

Accessories

ILC 2050 BI - Controller

2403160

https://www.phoenixcontact.com/us/products/2403160



Modular Inline controller for automation applications in the fields of building technology, infrastructure, and energy technology. Equipped with two logically separated IP address interfaces each with 2 integrated Fast Ethernet ports. Configurable assignment of the Ethernet ports for the use of the spanning-tree protocol, daisy chain and redundant ring structures for maximum availability. Four LAN, two USB, and two RS-485 interfaces are integrated. The data point connections can be extended with up to 63 Inline I/O modules: digital and analog, function terminals for DALI, pulse counting, MBUS or serial interfaces.

Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com