108 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122192-15 TNC Jack Straight Bulkhead - Rear Mount Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle Connector A			A Cable		Connector B			
135" 45°	Part #:	132245		Part #:	RG-174	Part #:	122192-15	
	Description:	SMA R/A BHD JK RG174 RG316 LMR100		Description:	RG-174 - PE 0.1	Description:	TNC BHD JK RG174 RG188 RG316 IP67 500	
	Description.	500		Dielectric:	PE	Туре:	TNC	
180°	Туре:	SMA		Shielding:	Shielding: Braid Gender:		Jack	
	Gender:	Jack		Diameter:	0.1	Body Type:	Straight	
225"	Body Type:	Right Angle		Impedance:	50 Ohm	Contact Type:	Crimp	
223 313	Contact Type:	Solder		Sheathing:	None	Polarity:	Standard 50 Ohm	
210	Polarity:	Standard		Testing:	Continuity Hi-Pot	Impedance:		
	Impedance:	50 Ohm		Length:	108 Inches	Mounting:	Bulkhead - Rear Mo	ount
	Mounting:	Bulkhead - Rear Mount		, i i i i i i i i i i i i i i i i i i i		Body Material: Brass		
	Body Material:	Brass				Body Finish:	Nickel	
	Body Finish:	Gold				IP Rating:	IP67	
D-Flat	IP Rating: None					Contact Material:	Phosphor Bronze	
Bulkhead	Bulkhead Contact Material: Beryllium Copper					Contact Finish:	Gold 11 GHz TNC Jack Straight BHD	
	Contact Finish:	Gold				Max. Freg.:		
	Max. Freq.:	12.4 GHz				Booting:		
	Booting:	SMA Jack Right Angle				Clocking:	0°	
			THE DRAWING MAN CONTAIN		Title:			UNLESS SPECIFIED
Amphenol CUSTOM CABLE			AND MUST NOT BE USED ITAL TO CUSTOM CABLE JCED OR TRANSCRIBED		ST-JK G174 108I	K G174 108I		
			CUSTOM CABLE INC. ACCEPTA ESTABLISHES AND AGREEMEN					ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES