



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 0.1 A

Business data

Article number	2896.0
Article name	SI 5x20 0,100A-F
GTIN (EAN)	4044211056216
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.96 g
Weight per piece (including packaging)	1 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

Technical data

Dimensions

Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm

Ratings

Rated voltage	250 V
Rated current	0.1 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Glass

Further technical data

Trigger characteristic	Fast-acting (F)
Rated breaking capacity	35 A @ AC 250 V
Voltage drop	2200 mV
Power loss (@ 1.5 In)	0.6 W
Melting integral I ² ts	0.0022 A ² s

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

2896.0 SI 5x20 0,100A-F



Approvals

Standards and regulations

Standards / specifications

IEC 60127-2/2 EN 60127-2/2 VDE 0820-2/2

Data sheet

2896.0 SI 5x20 0,100A-F



Media

Accessories
