

Ferrule - AI 1,5 -18 RD - 3241125

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrule, Sleeve length: 18 mm, Length: 24 mm, Color: red

The figure shows the version AI 1-8 RD

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	500 STK
Custom tariff number	85369010
Country of origin	Germany

Technical data

Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
------------	------------------------------------------------

Dimensions

Length (b)	24 mm
Maximum stripping length	21 mm
Sleeve length	18 mm
Inner dimension of the insulating collar (d)	3.4 mm
Ferrule diameter	1.8 mm
Insulating collar thickness	0.3 mm
Sleeve wall thickness	0.15 mm

General

Color	red
Components	free from silicone and halogen

Ferrule - Al 1,5 -18 RD - 3241125

Technical data

General


Flammability rating according to UL 94	HB
----------------------------------------	----

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	HB

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCl@ss 8.0	27400201
eCl@ss 9.0	27400201

ETIM

ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703

Ferrule - AI 1,5 -18 RD - 3241125

Classifications

UNSPSC

UNSPSC 13.2	27121703
-------------	----------

Approvals


Approvals

Approvals

CSA

Ex Approvals

Approval details

CSA  http://www.csagroup.org/us/en/services/testing-and-certification/certified-product-listing-247397
