

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 CONTACT MATERIAL: BRASS  
 SURFACE PLATING:  
 SILVER PLATING:  $\geq 2\mu\text{m}$   
 CONTACT RESISTANCE:  $\leq 0.5\text{m}\Omega$   
 WIRE RANGE:  $35\text{mm}^2$   
 OPERATION TEMPERATURE:  $-40\sim+125^\circ\text{C}$

注释:

1. 技术参数:  
 公针材料: 黄铜  
 表面电镀:  
 镀银:  $\geq 2\mu\text{m}$   
 接触电阻:  $\leq 0.5\text{m}\Omega$   
 接线范围:  $35\text{mm}^2$   
 工作温度:  $-40\sim+125^\circ\text{C}$

T2060001035-000	CHM-35	CHM-35, SILVER PLATING HMN-001公针 $35\text{mm}^2$ , 镀银	35	20
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE ( $\text{mm}^2$ ) 线规 ( $\text{mm}^2$ )	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang		
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu	NAME CHM-35 HM PIN CONTACT	
0 PLC $\pm$ -		PRODUCT SPEC 108-137057	SIZE	
1 PLC $\pm$ -		APPLICATION SPEC 114-137057	CAGE CODE	
2 PLC $\pm$ -		WEIGHT	DRAWING NO	
3 PLC $\pm$ -		Customer Drawing	RESTRICTED TO	
4 PLC $\pm$ -			A300779	
ANGLES $\pm$ -			SCALE 2:1	
FINISH			SHEET 1 OF 1	
MATERIAL			REV A1	
			DRAWING NO T2060001035000	

1470-19 (3/13)