

Han PushPull SCRJ WDF coupling



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 35 242 0333 |
| Specification | Han PushPull SCRJ WDF coupling |
| HARTING eCatalogue | https://b2b.harting.com/09352420333 |

Identification

| | |
|-----------------|---------------------------------|
| Category | Connectors |
| Series | Han [®] PushPull (V14) |
| Identification | SCRJ |
| Element | Panel feed through |
| Specification | AIDA compliant |
| Type of contact | SC contact |
| Features | Intuitive locking mechanism |

Version

| | |
|--------------------|------------------|
| Shielding | Unshielded |
| Number of contacts | 2 |
| Locking type | PushPull |
| Pack contents | Without contacts |

Technical characteristics

| | |
|--|----------------|
| Limiting temperature | -40 ... +70 °C |
| Mating cycles | ≥750 |
| Degree of protection acc. to IEC 60529 | IP65 IP67 |

Material properties

| | |
|-------------------------|---------------|
| Material (hood/housing) | Thermoplastic |
| Colour (hood/housing) | Black |



Pushing Performance
Since 1945

Material properties

| | |
|---|---------------|
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Naphthalene |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 61076-3-117 Variant 14 (V14) IEC 61754-24 Mating face |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals | DNV GL |
| PROFINET | Yes |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 15.62 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140054448 |
| eCl@ss | 27440114 Rectangular connector (for field assembly) |