


G50LAC-P04QF00-0000 series_l, type_g5



General information

| | |
|-------------------|---------------------|
| Part number | G50LAC-P04QF00-0000 |
| Termination | pcb |
| Size | 0 |
| Locking principle | break , push |
| Coding | a_key |



Contact insert description

| | |
|----------------------|--------------|
| Number of contacts | 4 |
| Contact type | sockets |
| Contact diameter | 07mm |
| Insulator material | peek |
| Termination | pcb |
| Termination diameter | 05mm |
| Data transmission | ethernet_100 |

reverse_gender_on_request

Technical information

| | | |
|--|----------|---------------|
| Max. creepage and air clearance distance | 08_mm | 10_mm |
| Nominal current single contact | 06_a | iec_60512_5_2 |
| Nominal current insert | 6 A | vde_0298_4 |
| Test voltage | 09_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| | |
|-----------------------|----------|
| Degree of protection* | ip50 |
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated_unmated

Material and surface treatments

| | |
|----------------|---------------|
| Housing | m_chrome |
| Contact | cu_alloy_gold |

data_text

safety_text_2

data_text

ul_text

illustrative_text