

CompuCableUSA

Providing Connectivity Solutions

specification		UL2464 26AWG*25C+D+AL. Mylar, OD:8.0mm Gray PVC HALF MATT		Picture														
Item		25C		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">Conductor</td> <td style="text-align: center;">AWG</td> <td colspan="2" style="text-align: center;">26AWG</td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">Material</td> <td colspan="2" style="text-align: center;">Tinned copper</td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">Cond. Size</td> <td colspan="2" style="text-align: center;">7/0.16TC±0.008mm</td> </tr> </table>			Conductor	AWG	26AWG			Material	Tinned copper			Cond. Size	7/0.16TC±0.008mm	
Conductor	AWG	26AWG																
	Material	Tinned copper																
	Cond. Size	7/0.16TC±0.008mm																
Insulation	Avg. Thick	0.23mm Ref																
	Material	SR-PVC																
	O. D	1.00±0.05mm																
	Color	1. BLACK; 2. BROWN; 3. RED; 4. ORANGE; 5. YELLOW; 6. GREEN; 7. BLUE; 8. PURPLE; 9. GRAY; 10. WHITE; 11. PINK; 12. LIGHT GREEN; 13. BLACK/WHITE; 14. BROWN/WHITE; 15. RED/WHITE; 16. ORANGE/WHITE; 17. GREEN/WHITE 18. BLUE/WHITE 19. PURPLE/WHITE; 20. RED/BLACK 21. ORANGE/BLACK 22. YELLOW/BLACK; 23. GREEN/BLACK 24. GRAY/BLACK 25. PINK/BLACK		Note	1. Rating:TEMP 80°C:Voltage: 300V 2. ConductorResistance:AT20°C MAX, 26AWG:148.94 Ω /KM 3. Insulation Resistance:DC500V MIN 10MΩ /Km; 4. Dieleatric Strength :AC:500V/1minute;													
intertwist	Drain	7/0.20TC±0.008mm Tinned copper																
	aluminum foil AL	25u*35±5mm >25% MIN																
Braid	Cond. Size	/																
	Shield Coverage	/		Rev	A/0:													
Jacket	Material Color	PVC N9C03016 VW-1/60P Gray (PT:430C)		Customer	CompuCablePlusUSA													
	O. D	8.0±0.15mm		Part.No:	BW-26AL-25G1K													
	Surface	HALF MATT		Part.No:														
Marking	E134689 AWM 2464 80°C 300V VW-1 (1") RoHS (1") RoHS2.0 (1") REACH (1") COMPLIANT			Rev:														
	height: 1.2MM	Color: BLACK	font: C1-18	(1")	Data:													