






Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de c FCI. Droits de reproduction FCI.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



PERFORMANCE CHARACTERISTICS


- CURRENT RATING 1.5A AT 20°C (FULLY LOADED)
- 1 A AT 70°C (FULLY LOADED)
- RATED VOLTAGE : 500 V AC (CONT /CONT)
- OPERATING TEMPERATURE : -55°C TO 125°C
- CONTACT RESISTANCE 20 MΩ MAX
- INSERTION FORCE : 0.75N MAX/CONT
- EXTRACTION FORCE : 0.15N MIN/CONT
- INSULATION RESISTANCE : 10<sup>4</sup> MΩ MIN

- 1. HM2R30PA5100-  
 LEAD FREE INDICATOR : LF=LEAD FREE(DIGIT 15&16)  
 PLATING CODE(DIGIT 13&14)

Plating code	Plating	Performance Level
AA	0.75um Au	IEC performance level 2(250mating cycles)orTELCORDIA C0
AB	1.25um Au	TELCORDIA UE

- 2. THIS PRODUCT IS CSA APPROVED. THIS PRODUCT IS UL RECOGNIZED.
- 3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A.201572.001
- 4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

LAY-OUT  
P.C.B.- HOLE



rev	ecn no	dr	date
A	DG09-0243	NZ	Jul-20-2009
B	DG10-0093	NZ	Mar-08-2010
C	DG10-0110	NZ	Jun-08-2010
-	-	-	-
-	-	-	-

Material			Spec ref		
Mat code			✓	tolerance 1DEC ± 0.2 1DEC 2DEC ± 0.1 2DEC ANGLES ± 1° HOEKEN	projection MM
Heattreat					
Plating/Finish					
Dr	Nickor Zuo	Jul-20-09	Product family	MILLIPACS	size A4
Eng	Nickor Zuo	Jul-20-09	Model Name	ECN	Scale 2.000
Chr	PeiMing Zheng	Jul-20-09	Model Revision	REL Level	
Appr	Joseph Hsia	Jul-20-09			
			title MPACS 5+2R RA RCP CONN TYPE C		dwg no BSC201418020
Pro/E file	catalog no	HM2R30PA5100----	CUSTOMER DRAWING		Rev. C
					sheet 1 of 1