

54010-1 ✓ ACTIVE

AMP | AMP CPC

TE Internal #: 54010-1

Cable Seal, Black, -55 – 110 °C [-67 – 230 °F] Operating Temperature, AMP CPC

[View on TE.com >](#)



Connectors > Connector Accessories > Connector Seals & Cavity Plugs > CPC Heat Shrink Strain Reliefs



Connector Seal & Plug Type: **Cable Seal**

Primary Product Color: **Black**

Operating Temperature (Max): **110 °C [230 °F]**

Operating Temperature Range: **-55 – 110 °C [-67 – 230 °F]**

[All CPC Heat Shrink Strain Reliefs \(7\)](#)

Features

Product Type Features

Connector Seal & Plug Type	Cable Seal
----------------------------	------------

Body Features

Primary Product Color	Black
-----------------------	-------

Mechanical Attachment

Thread Size	.625-24 UNEF-2B
-------------	-----------------

Dimensions

Compatible Cable Diameter Range	6.35 – 15.24 mm [.25 – .6 in]
---------------------------------	-------------------------------

Usage Conditions

Operating Temperature (Max)	110 °C [230 °F]
Operating Temperature Range	-55 – 110 °C [-67 – 230 °F]

Packaging Features

Packaging Quantity	50
Packaging Method	Carton

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer











This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Part # CAT-AM71-C83998M CPC Connectors, Series 2</p>	 <p>TE Part # CAT-AM71-C83998Y One-Piece Connector, Sealed, CPC Series 1</p>	 <p>TE Part # CAT-AM71-C83998K Circular Connector, Environmentally Sealed, CPC Series 6</p>	 <p>TE Part # 206516-1 CPC PLUG ASSEMBLY SIZE 11-4</p>
----------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------





Also in the Series | AMP CPC



Customers Also Bought





Documents

Product Drawings

[CPC STRAIN RELIEF,SIZE 11](#)

English

CAD Files

[3D PDF](#)

English

Customer View Model

[ENG_CVM_54010-1_AC.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_54010-1_AC.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_54010-1_AC.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_54010-1_AB.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_54010-1_AB.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_54010-1_AB.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[AMP Circular Connectors for Commercial Signal & Power Applications Continued](#)

English

Product Specifications

[Application Specification](#)

English



Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (U.S.)

English