Features

- N channel
- Enhancement mode
- Temperature sensor with thyristor characteristic
- The drain pin is electrically shorted to the tab



Pin	1	2	3
	G	D	S

Type	V_{DS}	I_D	$R_{DS(on)}$	Package	Ordering Code
BTS 112A	60 V	12 A	0.15 Ω	TO-220AB	C67078-S5014-A3

Maximum Ratings

Parameter	Symbol	Values	Unit
Drain-source voltage	V_{DS}	60	V
Drain-gate voltage, R_{GS} = 20 kΩ	V_{DGR}	60	
Gate-source voltage	V_{GS}	± 20	
Continuous drain current, T_C = 33 °C	I_D	12	A
ISO drain current T_C = 85 °C, V_{GS} = 10 V, V_{DS} = 0.5 V	$I_{D\text{-}ISO}$	2.5	
Pulsed drain current, T_C = 25 °C	$I_{D\ puls}$	48	
Short circuit current, T_j = – 55 ... + 150 °C	I_{SC}	27	
Short circuit dissipation, T_j = – 55 ... + 150 °C	P_{SCmax}	400	W
Power dissipation	P_{tot}	40	
Operating and storage temperature range	T_j, T_{stg}	– 55 ... + 150	°C
DIN humidity category, DIN 40 040	–	E	–
IEC climatic category, DIN IEC 68-1	–	55/150/56	
Thermal resistance Chip-case Chip-ambient	 $R_{th\ JC}$ $R_{th\ JA}$	 ≤ 3.1 ≤ 75	K/W

Electrical Characteristics

at T_j = 25 ˚C, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Static Characteristics					
Drain-source breakdown voltage V_{GS} = 0, I_D = 0.25 mA	$V_{(BR)DSS}$	60	–	–	V
Gate threshold voltage V_{GS} = V_{DS}, I_D = 1.0 mA	$V_{GS(th)}$	2.5	3.0	3.5	
Zero gate voltage drain current V_{GS} = 60 V, V_{DS} = 0 T_j = 25 °C T_j = 150 °C	I_{DSS}	 – –	 0.1 10	 1.0 100	µA
Gate-source leakage current V_{GS} = ± 20 V, V_{DS} = 0 T_j = 25 °C T_j = 150 °C	I_{GSS}	 – –	 10 2	 100 4	 nA µA
Drain-source on-state resistance V_{GS} = 10 V, I_D = 7.5 A	$R_{DS(on)}$	–	0.12	0.15	Ω
Dynamic Characteristics					
Forward transconductance $V_{DS} \geq 2 \times I_D \times R_{DS(on)max}$, I_D = 7.5 A	g_{fs}	3.0	5.7	–	S
Input capacitance V_{GS} = 0, V_{DS} = 25 V, f = 1 MHz	C_{iss}	–	360	480	pF
Output capacitance V_{GS} = 0, V_{DS} = 25 V, f = 1 MHz	C_{oss}	–	160	250	
Reverse transfer capacitance V_{GS} = 0, V_{DS} = 25 V, f = 1 MHz	C_{rss}	–	50	90	
Turn-on time t_{on}, (t_{on} = $t_{d(on)}$ + t_r) V_{CC} = 30 V, V_{GS} = 10 V, I_D = 3 A, R_{GS} = 50 Ω	$t_{d(on)}$	–	15	25	ns
	t_r	–	30	45	
Turn-off time t_{off}, (t_{off} = $t_{d(off)}$ + t_f) V_{CC} = 30 V, V_{GS} = 10 V, I_D = 3 A, R_{GS} = 50 Ω	$t_{d(off)}$	–	40	55	
	t_f	–	55	75	

Electrical Characteristics (cont'd)
at T_j = 25 °C, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Reverse Diode					
Continuous source current	I_S	–	–	12	A
Pulsed source current	I_{SM}	–	–	48	
Diode forward on-voltage I_F = 12 A, V_{GS} = 0 V	V_{SD}	– 	1.3 	1.6 	V
Reverse recovery time $I_F = I_S$, di_F/dt = 100 A/µs, V_R = 30 V	t_{rr}	– 	60 	– 	ns
Reverse recovery charge $I_F = I_S$, di_F/dt = 100 A/µs, V_R = 30 V	Q_{rr}	– 	0.1 	– 	µC
Temperature Sensor					
Forward voltage $I_{TS(on)}$ = 10 mA, T_j = – 55 ... + 150 °C Sensor override, $t_p \leq$ 100 µs T_j = – 55 ... + 160 °C	$V_{TS(on)}$	 – –	 1.4 –	 1.5 10	V
Forward current T_j = – 55 ... + 150 °C Sensor override, $t_p \leq$ 100 µs T_j = – 55 ... + 160 °C	$I_{TS(on)}$	 – –	 – –	 10 600	mA
Holding current, $V_{TS(off)}$ = 5.0 V, T_j = 25 °C T_j = 150 °C	I_H	0.05 0.05	0.1 0.2	0.5 0.3	
Switching temperature V_{TS} = 5.0 V	$T_{TS(on)}$	 150	 –	 –	°C
Turn-off time V_{TS} = 5.0 V, $I_{TS(on)}$ = 2 mA	t_{off}	 0.5	 –	 2.5	µs

Examples for short-circuit protection

at T_j = – 55 ... + 150 °C, unless otherwise specified.

Parameter	Symbol	Examples			Unit
		1	2	–	
Drain-source voltage	V_{DS}	15	30	–	V
Gate-source voltage	V_{GS}	6.8	5.0	–	
Short-circuit current	I_{SC}	27	11	–	A
Short-circuit dissipation	P_{SC}	400	330	–	W
Response time T_j = 25 °C, before short circuit	$t_{SC(off)}$	20	20	–	ms

Short-circuit protection $I_{SC} = f(V_{DS})$
Parameter: V_{GS}
Diagram to determine I_{SC} for T_j = –55 ... +150°C



Max. gate voltage $V_{GS(SC)} = f(V_{DS})$
Parameter: T_j = – 55 ... + 150 °C



Max. power dissipation $P_{tot} = f(T_C)$



Typ. drain-source on-state resistance
$R_{DS(on)} = f(I_D)$
Parameter: V_{GS}



Typical output characteristics $I_D = f(V_{DS})$
Parameter: t_p = 80 s



Safe operating area $I_D = f(V_{DS})$
Parameter: D = 0.01, T_C = 25 °C



Drain-source on-state resistance
$R_{DS(on)} = f(T_j)$
Parameter: I_D = 5 A, V_{GS} = 10 V



Gate threshold voltage $V_{GS(th)} = f(T_j)$
Parameter: $V_{DS} = V_{GS}$, I_D = 1 mA



Typ. transfer characteristic
$I_D = f(V_{GS})$
Parameter: t_p = 80 µs, V_{DS} = 25 V



Typ. transconductance $g_{fs} = f(I_D)$
Parameter: t_p = 80 µs, V_{DS} = 25 V



Continuous drain current $I_D = f(T_C)$
Parameter: $V_{GS} \geq -10$ V



Forward characteristics of reverse diode
$I_F = f(V_{SD})$
Parameter: T_j, t_p = 80 µs



Typ. gate-source leakage current
$I_{GSS} = f(T_C)$
Parameter: $V_{GS} = -20$ V, $V_{DS} = 0$



Typ. capacitances $C = f(V_{DS})$
Parameter: $V_{GS} = 0$, $f = 1$ MHz



Transient thermal impedance $Z_{thJC} = f(t_p)$
Parameter: $D = t_p/T$



TO 220 AB	Ordering Code
Standard	C67078-S5014-A3



1) punch direction, burr max. 0.04
2) dip tinning
3) max. 14.5 by dip tinning press burr max. 0.05

TO 220 AB	Ordering Code
SMD Version E 3045	C67078-S5014-A4
Tape & reel E 3045 A	C67078-S5014-A5



1) shear and punch direction no burrs this surface

Edition 04.97

**Published by Infineon Technologies AG,
St.-Martin-Strasse 53,
D-81541 München, Germany**

**© Infineon Technologies AG 2000.
All Rights Reserved.**

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.